
CALCEPH - C language

Release 4.0.4

M. Gastineau, J. Laskar, A. Fienga, H. Manche

Jan 01, 2025

CONTENTS

1	Introduction	3
2	Installation	5
2.1	Quick instructions	5
2.2	Requirements	6
2.3	Detailed instructions	6
3	Library interface	9
3.1	A simple example program	9
3.2	Headers and Libraries	9
3.2.1	Compilation on a Unix-like system	10
3.2.2	Compilation on a Windows system	10
3.3	Types	10
3.4	Constants	10
4	Multiple file access functions	13
4.1	Time notes	13
4.2	Thread notes	13
4.3	Usage	13
4.4	Functions	13
4.4.1	calceph_open	13
4.4.2	calceph_open_array	14
4.4.3	calceph_prefetch	15
4.4.4	calceph_isthreadsafe	16
4.4.5	calceph_compute	16
4.4.6	calceph_compute_unit	18
4.4.7	calceph_orient_unit	20
4.4.8	calceph_rotangmom_unit	21
4.4.9	calceph_compute_order	23
4.4.10	calceph_orient_order	25
4.4.11	calceph_rotangmom_order	27
4.4.12	calceph_getconstant	29
4.4.13	calceph_getconstantsd	29
4.4.14	calceph_getconstantvd	30
4.4.15	calceph_getconstantss	31
4.4.16	calceph_getconstantvs	32
4.4.17	calceph_getconstantcount	32
4.4.18	calceph_getconstantindex	33
4.4.19	calceph_getfileversion	34
4.4.20	calceph_getidbyname	34

4.4.21	calceph_getnamebyidss	35
4.4.22	calceph_gettimescale	36
4.4.23	calceph_gettimespan	37
4.4.24	calceph_getpositionrecordcount	38
4.4.25	calceph_getpositionrecordindex	38
4.4.26	calceph_getpositionrecordindex2	39
4.4.27	calceph_getorientrecordcount	40
4.4.28	calceph_getorientrecordindex	41
4.4.29	calceph_getorientrecordindex2	42
4.4.30	calceph_close	43
5	Error functions	45
5.1	Usage	45
5.2	calceph_seterrorhandler	46
6	Miscellaneous functions	47
6.1	calceph_getmaxsupportedorder	47
6.2	calceph_getversion_str	47
7	NAIF identification numbers	49
7.1	Sun and planetary barycenters	49
7.2	Coordinate Time ephemerides	49
7.3	Planet centers and satellites	49
7.4	Comets	53
8	Release notes	57
9	Reporting bugs	63
10	CALCEPH Library Copying conditions	65

This manual documents how to install and use the CALCEPH Library using the C interface.

Authors : M. Gastineau, J. Laskar, A. Fienga, H. Manche

INTRODUCTION

The CALCEPH Library is designed to access the binary planetary ephemeris files, such INPOPxx and JPL DExxx ephemeris files, (called 'original JPL binary' or 'INPOP 2.0 or 3.0 binary' ephemeris files in the next sections) and the SPICE kernel files (called 'SPICE' ephemeris files in the next sections). At the moment, supported SPICE files are :

- text Planetary Constants Kernel (KPL/PCK) files
- binary PCK (DAF/PCK) files.
- binary SPK (DAF/SPK) files containing segments of type 1, 2, 3, 5, 8, 9, 12, 13, 14, 17, 18, 20, 21, 102, 103 and 120.
- meta kernel (KPL/MK) files.
- frame kernel (KPL/FK) files. Only a basic support is provided.

This library provides a C interface and, optionally, the Fortran 77 or 2003, Python and Octave/Matlab interfaces, to be called by the application.

Two groups of functions enable the access to the ephemeris files :

- Multiple file access functions

These functions provide access to many ephemeris file at the same time.

- Single file access functions

These functions provide access to only one ephemeris file at the same time. They are provided to make transition easier from the JPL functions, such as *PLEPH*, to this library.

This library could access to the following ephemeris

- INPOP06 or later
- DE200
- DE403 or later
- EPM2011 or later

Although computers have different endianness (order in which integers are stored as bytes in computer memory), the library could handle the binary ephemeris files with any endianness. This library automatically swaps the bytes when it performs read operations on the ephemeris file.

The internal format of the original JPL binary planetary ephemeris files is described in the paper :

- David Hoffman : 1998, A Set of C Utility Programs for Processing JPL Ephemeris Data, <ftp://ssd.jpl.nasa.gov/pub/eph/export/C-versions/hoffman/EphemUtilVer0.1.tar>

The 'INPOP 2.0 binary' file format for planetary ephemeris files is described in the paper :

- M. Gastineau, J. Laskar, A. Fienga, H. Manche : 2012, INPOP binary ephemeris file format - version 2.0 https://www.imcce.fr/inpop/inpop_file_format_2_0.pdf

The 'INPOP 3.0 binary' file format for planetary ephemeris files is described in the paper :

- M. Gastineau, J. Laskar, A. Fienga, H. Manche : 2017, INPOP binary ephemeris file format - version 3.0 https://www.imcce.fr/inpop/inpop_file_format_3_0.pdf

INSTALLATION

The following section describes the installation of the **C** and **Fortran** interface of the library. If you want to install the interface for another programming language, you have to follow the instructions of the manual of that language.

2.1 Quick instructions

Here are the quick steps needed to install the library on Unix systems. In the following instructions, you must replace */home/mylogin/mydir* by the directory location where you want to install calceph.

If you use the gnu gcc and gfortran compilers, the steps are :

```
tar xzf calceph-4.0.4.tar.gz
cd calceph-4.0.4
mkdir build
cd build
CC=gcc FC=gfortran cmake -DCMAKE_INSTALL_PREFIX=/home/mylogin/mydir ..
cmake --build . --target all
cmake --build . --target test
cmake --build . --target install
```

If you use the Intel c++ and fortran compilers, the steps are :

```
tar xzf calceph-4.0.4.tar.gz
cd calceph-4.0.4
mkdir build
cd build
CC=icc FC=ifort cmake -DCMAKE_INSTALL_PREFIX=/home/mylogin/mydir ..
cmake --build . --target all
cmake --build . --target test
cmake --build . --target install
```

If you use the llvm clang and flang compilers, the steps are :

```
tar xzf calceph-4.0.4.tar.gz
cd calceph-4.0.4
mkdir build
cd build
CC=clang FC=flang cmake -DCMAKE_INSTALL_PREFIX=/home/mylogin/mydir ..
cmake --build . --target all
cmake --build . --target test
cmake --build . --target install
```

If you use the Microsoft Visual C++ compilers, the steps are :

```
tar xzf calceph-4.0.4.tar.gz
```

```
cd calceph-4.0.4
mkdir build
cd build
cmake -G "NMake Makefiles" -DCMAKE_INSTALL_PREFIX=/home/mylogin/mydir ..
cmake --build . --target all
cmake --build . --target test
cmake --build . --target install
```

2.2 Requirements

You need the following software to build the library

- *CMake*, available at <https://cmake.org>
- a C compiler, such as *gcc* or *clang* or the Microsoft Visual C++ compiler.
- a Fortran compiler, such as *gfortran* or *ifort*, compliant with the Fortran 77, respectively 2003, specifications is required to compile the fortran-77/90/95, respectively fortran-2003, interface of the library.

The additional tools are required to build the documentation

- the python packages : sphinx, six, sphinx-fortran, sphinx-rtd-theme, sphinxcontrib-matlabdomain. They can be installed using the command pip3

```
pip3 install Sphinx six sphinx-fortran sphinx-rtd-theme sphinxcontrib-matlabdomain
```

- pdflatex, available with the software LaTeX, if PDF documentation is requested (-DENABLE_PDF=ON).

Additional requirements for the Microsoft Visual C++ compiler

In addition to the Microsoft Visual C++ compiler and *CMake*, you also need the Universal CRT SDK or a Windows SDK.

The "Universal CRT (C runtime) SDK" or a "Windows SDK" are now provided with the Microsoft Visual Studio. You should verify that "Universal CRT (C runtime) SDK" or a "Windows SDK" is selected in the "Visual Studio Installer".

2.3 Detailed instructions

Here are the detailed steps needed to install the library :

- tar xzf calceph-4.0.4.tar.gz
- cd calceph-4.0.4
- mkdir build
- cd build

If you are on a Unix-like system :

- cmake ..

If you are using the Microsoft Visual C++ compiler :

- cmake -G "NMake Makefiles" ..

Running *cmake* might take a while. While running, it prints some messages telling which features it is checking for.

cmake recognizes the following options to control how it operates. The options must specified just after the name of software cmake : *cmake <options> ..*

- `-DENABLE_FORTRAN={ON|OFF}`
Enable or disable the fortran-77 and fortran-2003 interface. The default is *ON*.
- `-DENABLE_THREAD={ON|OFF}`
Enable or disable the thread-safe version of the functions `calceph_sopen()` and `calceph_scompute()`, ... and concurrent access to the function `calceph_compute()`, The default is *ON*.
- `-DBUILD_SHARED_LIBS={ON|OFF}`
Enable or disable the generation of the shared library, otherwise static library is build. The default is *OFF*, static library is built by default.
- `-DENABLE_DOC={ON|OFF}`
Enable or disable the generation of the html documentation and its installation. The default is *OFF*.
- `-DENABLE_PDF={ON|OFF}`
Enable or disable the generation of the PDF documentation and its installation. The default is *OFF*.
- `-DCMAKE_INSTALL_PREFIX= dir`
Use *dir* as the installation prefix. See the command *make install* for the installation names.

The default compilers could be changed using the variable `CC` for C compiler and `FC` for the Fortran compiler. The default compiler flags could be changed using the variable `CFLAGS` for C compiler and `FCFLAGS` for the Fortran compiler.

Note

The option `-DENABLE_PYTHON...` or `-DENABLE_MEX_OCTAVE...` should not be used. They are reserved for the installation of the python or mex interface.

- `cmake --build . --target all`

This compiles the CALCEPH Library in the working directory.

- `cmake --build . --target test`

This will make sure that the CALCEPH Library was built correctly.

If you get error messages, please report them to inpop.imcce@obspm.fr (see *Reporting bugs*, for information on what to include in useful bug reports).

- `cmake --build . --target doc`

This builds the documentation of the CALCEPH Library if `ENABLE_DOC` was set to *ON*.

- `cmake --build . --target install`

This will copy the files `calceph.h`, `calceph.mod` and `f90calceph.h` to the directory `/usr/local/include`, the file `libcalceph.a`, `libcalceph.so` to the directory `/usr/local/lib`, and the documentations files to the directory `/usr/local/doc/calceph/` (or if you passed the `-DCMAKE_INSTALL_PREFIX=` option to *cmake*, using the prefix directory given as argument to `-DCMAKE_INSTALL_PREFIX=` instead of `/usr/local`). Note: you need write permissions on these directories.

Other *make* Targets

There are some other useful make targets:

- *clean*

Delete all object files and archive files, but not the configuration files.

LIBRARY INTERFACE

3.1 A simple example program

The following example program shows the typical usage of the C interface.

Other examples using the C interface can be found in the directory *examples* of the library sources.

```
#include <stdio.h>
#include "calceph.h"

int main(void)
{
    double AU;
    t_calcephbin *peph;

    peph = calceph_open("example1.dat");
    if (peph)
    {
        if (calceph_getconstant(peph, "AU", &AU))
        {
            printf("AU=%23.16E\n", AU);
        }

        calceph_close(peph);
    }
    return 0;
}
```

3.2 Headers and Libraries

All declarations needed to use CALCEPH Library are collected in the include file `calceph.h`. It is designed to work with both C and C++ compilers.

You should include that file in any program using the CALCEPH library:

```
#include <calceph.h>
```

3.2.1 Compilation on a Unix-like system

All programs using CALCEPH must link against the `libcalceph` library. On Unix-like system this can be done with `-lcalceph`, for example

```
gcc myprogram.c -o myprogram -lcalceph
```

If CALCEPH Library has been installed to a non-standard location then it may be necessary to use `-I` and `-L` compiler options to point to the right directories, and some sort of run-time path for a shared library.

3.2.2 Compilation on a Windows system

- Using the Windows SDK

All programs using CALCEPH must link against the `libcalceph.lib`. On Windows system this can be done with `libcalceph.lib`, for example

```
cl.exe /out:myprogram myprogram.c libcalceph.lib
```

If CALCEPH Library has been installed to a non-standard location then it may be necessary to use `/I` and `/LIBPATH:` compiler options to point to the right directories.

- Using the MinGW

All programs using CALCEPH must link against the `libcalceph` library. On the MinGW system, this can be done with `-lcalceph`, for example

```
gcc.exe myprogram.c -o myprogram -lcalceph
```

If CALCEPH Library has been installed to a non-standard location then it may be necessary to use `-I` and `-L` compiler options to point to the right directories, and some sort of run-time path for a shared library.

3.3 Types

type `t_calcephbin`

This type contains all information to access a single ephemeris file or a set of files to be used together.

type `t_calceph_charvalue`

This type is a array of characters to store the value of the constants as a string.

3.4 Constants

`CALCEPH_MAX_CONSTANTNAME`

This integer defines the maximum number of characters, including the trailing `'\0'`, that the name of a constant, available from the ephemeris file, could contain.

`CALCEPH_MAX_CONSTANTVALUE`

This integer defines the maximum number of characters, including the trailing `'\0'`, that the value of a constant, available from the ephemeris file, could contain if the value is stored as a string of characters.

`CALCEPH_VERSION_MAJOR`

This integer constant defines the major revision of this library. It can be used to distinguish different releases of this library.

CALCEPH_VERSION_MINOR

This integer constant defines the minor revision of this library. It can be used to distinguish different releases of this library.

CALCEPH_VERSION_PATCH

This integer constant defines the patch level revision of this library. It can be used to distinguish different releases of this library.

```
#if (CALCEPH_VERSION_MAJOR>=2)
    || (CALCEPH_VERSION_MAJOR>=3 && CALCEPH_VERSION_MINOR>=2)
...
#endif
```

CALCEPH_VERSION_STRING

This C null-terminated string constant is the version of the library, which can be compared to the result of `calceph_getversion` to check at run time if the header file and library used match:

```
char version[CALCEPH_MAX_CONSTANTNAME];
calceph_getversion_str(version);
if (strcmp (version, CALCEPH_VERSION_STRING)!=0)
fprintf (stderr, "Warning: header and library do not match\n");
```

Note: Obtaining different strings is not necessarily an error, as in general, a program compiled with some old CALCEPH version can be dynamically linked with a newer CALCEPH library version (if allowed by the operating system).

CALCEPH_ASTEROID

This integer defines the offset value for the asteroids that must be used as target or center for the computation functions, such as `calceph_compute()`.

The following constants specify in which units are expressed the output of the computation functions, such as `calceph_compute_unit()`:

CALCEPH_UNIT_AU

This integer defines that the unit of the positions and velocities is expressed in astronomical unit.

CALCEPH_UNIT_KM

This integer defines that the unit of the positions and velocities is expressed in kilometer.

CALCEPH_UNIT_DAY

This integer defines that the unit of the velocities or the quantity TT-TDB or TCG-TCB is expressed in day (one day=86400 seconds).

CALCEPH_UNIT_SEC

This integer defines that the unit of the velocities or the quantity TT-TDB or TCG-TCB is expressed in second.

CALCEPH_UNIT_RAD

This integer defines that the unit of the angles is expressed in radian.

CALCEPH_OUTPUT_EULERANGLES

This integer defines that the output array contains the euler angles.

CALCEPH_OUTPUT_NUTATIONANGLES

This integer defines that the output array contains the nutation angles.

CALCEPH_USE_NAIFID

This integer defines that the NAIF identification numbers are used as target or center for the computation functions, such as *calceph_compute_unit()*.

The following constants specify the type of segments for the functions, such as *calceph_getmaxsupportedorder()* :

CALCEPH_SEGTYPE_ORIG_0

This integer defines the type of segment for the original INPOP/JPL DE file format.

CALCEPH_SEGTYPE_SPK_1

CALCEPH_SEGTYPE_SPK_2

CALCEPH_SEGTYPE_SPK_3

CALCEPH_SEGTYPE_SPK_5

CALCEPH_SEGTYPE_SPK_8

CALCEPH_SEGTYPE_SPK_9

CALCEPH_SEGTYPE_SPK_12

CALCEPH_SEGTYPE_SPK_13

CALCEPH_SEGTYPE_SPK_14

CALCEPH_SEGTYPE_SPK_17

CALCEPH_SEGTYPE_SPK_18

CALCEPH_SEGTYPE_SPK_19

CALCEPH_SEGTYPE_SPK_20

CALCEPH_SEGTYPE_SPK_21

CALCEPH_SEGTYPE_SPK_102

CALCEPH_SEGTYPE_SPK_103

CALCEPH_SEGTYPE_SPK_120

This integer defines the type of segments (1, 2, 3, 5, 8, 9, 12, 13, 14, 17, 18, 20, 21, 102, 103 and 120) for the SPICE Kernel files.

MULTIPLE FILE ACCESS FUNCTIONS

The following group of functions should be the preferred method to access to the library. They allow to access to multiple ephemeris files at the same time, even by multiple threads.

When an error occurs, these functions execute error handlers according to the behavior defined by the function *calceph_seterrorhandler()*.

4.1 Time notes

The functions *calceph_compute()*, *calceph_compute_unit()*, *calceph_compute_order()*, *calceph_orient_unit()*, ... only accept a date expressed in the same timescale as the ephemeris files, which can be retrieved using the function *calceph_gettimescale()*. Ephemeris files are generally expressed using the timescale TDB. If a date, expressed in the TT (Terrestrial Time) timescale, is supplied to them, these functions will return an erroneous position of the order of several tens of meters for the planets. If a date, expressed in the Coordinated Universal Time (UTC), is supplied to them, these functions will return a very large erroneous position over several thousand kilometers for the planets.

4.2 Thread notes

If the standard I/O functions such as **fread** are not reentrant then the CALCEPH I/O functions using them will not be reentrant either.

It's safe for two threads to call the functions with the same object of type *t_calcephbin* if and only if the function *calceph_isthreadsafe()* returns a non-zero value. A previous call to the function *calceph_prefetch()* is required for the function *calceph_isthreadsafe()* to return a non-zero value.

It's safe for two threads to access simultaneously to the same ephemeris file with two different objects of type *t_calcephbin*. In this case, each thread must open the same file.

4.3 Usage

The following examples, that can be found in the directory *examples* of the library sources, show the typical usage of this group of functions.

The example in C language is `cmultiple.c`.

4.4 Functions

4.4.1 calceph_open

t_calcephbin *calceph_open(const char *filename)

Parameters

- **filename** -- pathname of the file

Returns

ephemeris descriptor. This value is NULL if an error occurs, otherwise non-NULL value.

This function opens the file whose pathname is the string pointed to by filename, reads the two header blocks of this file and returns an ephemeris descriptor associated to it. This file must be compliant to the format specified by the 'original JPL binary', 'INPOP 2.0 binary' or 'SPICE' ephemeris file. At the moment, supported SPICE files are the following :

- text Planetary Constants Kernel (KPL/PCK) files
- binary PCK (DAF/PCK) files.
- binary SPK (DAF/SPK) files containing segments of type 1, 2, 3, 5, 8, 9, 12, 13, 14, 17, 18, 20, 21, 102, 103 and 120.
- meta kernel (KPL/MK) files.
- frame kernel (KPL/FK) files. Only a basic support is provided.

Just after the call of *calceph_open()*, the function *calceph_prefetch()* should be called to accelerate future computations.

The function *calceph_close()* must be called to free allocated memory by this function.

The following example opens the ephemeris file example1.dat and example2.dat

```
t_calcephbin *peph1;
t_calcephbin *peph2;
peph1 = calceph_open("example1.dat");
peph2 = calceph_open("example2.dat");
if (peph1 && peph2)
{
    calceph_prefetch(peph1);
    calceph_prefetch(peph2);
    /*
     ... computation ...
    */
}
/* close the files */
if (peph1) calceph_close(peph1);
if (peph2) calceph_close(peph2);
```

4.4.2 calceph_open_array

t_calcephbin *calceph_open_array(int n, const char *array_filename[])

Parameters

- **n** -- number of files
- **array_filename** -- array of pathname of the files

Returns

ephemeris descriptor. This value is NULL if an error occurs, otherwise non-NULL value.

This function opens n files whose pathnames are the string pointed to by `array_filename`, reads the header blocks of these files and returns a single ephemeris descriptor associated to them.

These files must have the same type (e.g., all files are SPICE files or original JPL files). This file must be compliant to the format specified by the 'original JPL binary', 'INPOP 2.0 or 3.0 binary' or 'SPICE' ephemeris file. At the moment, supported SPICE files are the following :

- text Planetary Constants Kernel (KPL/PCK) files
- binary PCK (DAF/PCK) files.
- binary SPK (DAF/SPK) files containing segments of type 1, 2, 3, 5, 8, 9, 12, 13, 14, 17, 18, 20, 21, 102, 103 and 120.
- meta kernel (KPL/MK) files.
- frame kernel (KPL/FK) files. Only a basic support is provided.

The single descriptor internally maintains a table to respond to the following queries for computing the position-velocity vector between bodies present in these different files.

Just after the call of `calceph_open_array()`, the function `calceph_prefetch()` should be called to accelerate future computations.

The function `calceph_close()` must be called to free allocated memory by this function.

The following example opens the ephemeris file `example1.bsp` and `example1.tpc`

```
const char *filearr[2]= {"example1.bsp", "example1.tpc"};
t_calcephbin *peph;

peph = calceph_open_array(2, filearr);
if (peph)
{
    /* ... computation ... */
    calceph_close(peph);
}
```

4.4.3 calceph_prefetch

int `calceph_prefetch`(*t_calcephbin* *eph)

Parameters

- **eph** -- ephemeris descriptor

Returns

0 if an error occurs, otherwise non-zero value.

This function prefetches to the main memory all files associated to the ephemeris descriptor *eph*. This prefetching operation will accelerate the further computations performed with `calceph_compute()`, `calceph_compute_unit()`, `calceph_compute_order()`, `calceph_orient_unit()`,

It requires that the file is smaller than the main memory. If multiple threads (e.g. threads of openMP or Posix Pthreads) prefetch the data for the same ephemeris file, the used memory will remain the same as if the prefetch operation was done by a single thread if and if the endianness of the file is the same as the computer and if the operating system, such as Linux, MacOS X other unix, supports the function `mmap`.

4.4.4 calceph_isthreadsafe

int `calceph_isthreadsafe`(*t_calcephbin* *eph)

Parameters

- **eph** -- ephemeris descriptor

Returns

returns 1 if multiple threads can access the same ephemeris ephemeris descriptor, otherwise 0.

This function returns 1 if multiple threads can access the same ephemeris ephemeris descriptor, otherwise 0.

A previous call to the function `calceph_prefetch()` is required, and the library should be compiled with **--enable-thread=yes** on Unix-like operating system, for the function `calceph_isthreadsafe()` to return a non-zero value. If the file is not encoded with the same endian as the current hardware, then function may return 0.

If this function returns 1, several threads may use the same ephemeris descriptor for the computational functions `calceph_compute()`, It allows to use the same object for the parallel loops.

4.4.5 calceph_compute

int `calceph_compute`(*t_calcephbin* *eph, double JD0, double time, int target, int center, double PV[6])

Parameters

- **eph** -- ephemeris descriptor
- **JD0** -- Integer part of the Julian date (TDB or TCB)
- **time** -- Fraction part of the Julian date (TDB or TCB)
- **target** -- The body or reference point whose coordinates are required (see the list, below).
- **center** -- The origin of the coordinate system (see the list, below). If *target* is 14, 15, 16 or 17 (nutations, libration, TT-TDB or TCG-TCB), *center* must be 0.
- **PV** -- Depending on the target value, an array to receive the cartesian position (x,y,z) and the velocity (xdot, ydot, zdot), or a time scale transformation value, or the angles of the librations of the Moon and their derivatives, or the nutation angles and their derivatives.

Returns

0 if an error occurs, otherwise non-zero value.

This function reads, if needed, in the ephemeris file associated to *eph* and interpolates a single object, usually the position and velocity of one body (*target*) relative to another (*center*) for the time $JD0+time$ and stores the results to *PV*. The ephemeris file associated to *eph* must have been previously opened with the function `calceph_open()`.

The returned array *PV* has the following properties

- If the target is *TT-TDB*, only the first element of this array will get the result. The time scale transformation TT-TDB is expressed in seconds.
- If the target is *TCG-TCB*, only the first element of this array will get the result. The time scale transformation TCG-TCB is expressed in seconds.
- If the target is *Librations*, the array contains the angles of the librations of the Moon and their derivatives. The angles of the librations of the Moon are expressed in radians and their derivatives are expressed in radians per day.
- If the target is *Nutations*, the array contains the nutation angles and their derivatives. The nutation angles are expressed in radians and their derivatives are expressed in radians per day.

- Otherwise the returned values is the cartesian position (x,y,z), expressed in Astronomical Unit (au), and the velocity (xdot, ydot, zdot), expressed in Astronomical Unit per day (au/day).

The date (JD0, time) should be expressed in the same timescale as the ephemeris files, which can be retrieved using the function `calceph_gettimescale()`. To get the best numerical precision for the interpolation, the time is splitted in two floating-point numbers. The argument `JD0` should be an integer and `time` should be a fraction of the day. But you may call this function with `time=0` and `JD0`, the desired time, if you don't take care about numerical precision.

Warning

If a date, expressed in the Coordinated Universal Time (UTC), is supplied to this function, a very large erroneous position will be returned.

The possible values for `target` and `center` are :

value	meaning
1	Mercury Barycenter
2	Venus Barycenter
3	Earth
4	Mars Barycenter
5	Jupiter Barycenter
6	Saturn Barycenter
7	Uranus Barycenter
8	Neptune Barycenter
9	Pluto Barycenter
10	Moon
11	Sun
12	Solar Sytem barycenter
13	Earth-moon barycenter
14	Nutation angles
15	Librations
16	TT-TDB
17	TCG-TCB
asteroid number + CALCEPH_ASTEROID	asteroid

These accepted values by this function are the same as the value for the JPL function `PLEPH`, except for the values `TT-TDB`, `TCG-TCB` and asteroids.

For example, the value "CALCEPH_ASTEROID+4" for target or center specifies the asteroid Vesta.

The following example prints the heliocentric coordinates of Mars at time=2442457.5 and at 2442457.9

```
int res;
int j;
double jd0=2442457;
double dt1=0.5E0;
double dt2=0.9E0;
t_calcephbin *peph;
double PV[6];

/* open the ephemeris file */
peph = calceph_open("example1.dat");
```

(continues on next page)

(continued from previous page)

```

if (peph)
{
    /* the heliocentric coordinates of Mars */
    calceph_compute(peph, jd0, dt1, 4, 11, PV);
    for(j=0; j<6; j++) printf("%23.16E\n", PV[j]);

    calceph_compute(peph, jd0, dt2, 4, 11, PV);
    for(j=0; j<6; j++) printf("%23.16E\n", PV[j]);

    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.6 calceph_compute_unit

int **calceph_compute_unit**(*t_calcephbin* *eph, double JD0, double time, int target, int center, int unit, double PV[6])

Parameters

- **eph** -- ephemeris descriptor
- **JD0** -- Integer part of the Julian date (TDB or TCB)
- **time** -- Fraction part of the Julian date (TDB or TCB)
- **target** -- The body or reference point whose coordinates are required. The numbering system depends on the parameter unit.
- **center** -- The origin of the coordinate system. The numbering system depends on the parameter unit.
- **unit** --
The units of PV.
This integer is a sum of some unit constants (CALCEPH_UNIT_???) and/or the constant *CALCEPH_USE_NAIFID*.
If the unit contains *CALCEPH_USE_NAIFID*, the NAIF identification numbering system is used for the target and the center (*NAIF identification numbers* for the list).
If the unit doesnot contain *CALCEPH_USE_NAIFID*, the old number system is used for the target and the center (see the list in the function *calceph_compute()*).
- **PV** -- Depending on the target value, an array to receive the cartesian position (x,y,z) and the velocity (xdot, ydot, zdot), or a time scale transformation value, or the angles of the librations of the Moon and their derivatives, or the nutation angles and their derivatives.

Returns

0 if an error occurs, otherwise non-zero value.

This function is similar to the function *calceph_compute()*, except that the units of the output are specified.

This function reads, if needed, in the ephemeris file associated to *eph* and interpolates a single object, usually the position and velocity of one body (*target*) relative to another (*center*) for the time *JD0+time* and stores the results to *PV*. The ephemeris file associated to *eph* must have been previously opened with the function *calceph_open()*. The output values are expressed in the units specified by *unit*.

This function checks the units if invalid combinations of units are given to the function.

The date (JD0, time) should be expressed in the same timescale as the ephemeris files, which can be retrieved using the function `calceph_gettimescale()`.

Warning

If a date, expressed in the Coordinated Universal Time (UTC), is supplied to this function, a very large erroneous position will be returned.

The returned array *PV* has the following properties

- If the target is the time scale transformation TT-TDB, only the first element of this array will get the result.
- If the target is the time scale transformation TCG-TCB, only the first element of this array will get the result.
- If the target is *Librations*, the array contains the angles of the librations of the Moon and their derivatives.
- If the target is *Nutations*, the array contains the nutation angles and their derivatives.
- Otherwise the returned value is the cartesian position (x,y,z) and the velocity (xdot, ydot, zdot).

The values stored in the array *PV* are expressed in the following units

- The position and velocity are expressed in Astronomical Unit (au) if unit contains `CALCEPH_UNIT_AU`.
- The position and velocity are expressed in kilometers if unit contains `CALCEPH_UNIT_KM`.
- The velocity, TT-TDB, TCG-TCB, the derivatives of the angles of the nutation, or the derivatives of the librations of the Moon or are expressed in days if unit contains `CALCEPH_UNIT_DAY`.
- The velocity, TT-TDB, TCG-TCB, the derivatives of the angles of the nutation, or the derivatives of the librations of the Moon are expressed in seconds if unit contains `CALCEPH_UNIT_SEC`.
- The angles of the librations of the Moon or the nutation angles are expressed in radians if unit contains `CALCEPH_UNIT_RAD`.

For example, to get the position and velocities expressed in kilometers and kilometers/seconds, the unit must be set to `CALCEPH_UNIT_KM + CALCEPH_UNIT_SEC`.

The following example prints the heliocentric coordinates of Mars at time=2442457.5

```
int j;
double jd0=2442457;
double dt1=0.5E0;
t_calcephbin *peph;
double PV[6];

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* the heliocentric coordinates of Mars in km and km/s */
    calceph_compute_unit(peph, jd0, dt1, 4, 11,
                        CALCEPH_UNIT_KM+CALCEPH_UNIT_SEC,
                        PV);
    for(j=0; j<6; j++) printf("%23.16E\n", PV[j]);

    /* compute same quantity as the previous call using NAIF ID */
    calceph_compute_unit(peph, jd0, dt1,
                        NAIFID_MARS_BARYCENTER,
```

(continues on next page)

(continued from previous page)

```

        NAIFID_SUN,
        CALCEPH_USE_NAIFID+CALCEPH_UNIT_KM
        +CALCEPH_UNIT_SEC,
        PV);
    for(j=0; j<6; j++) printf("%23.16E\n", PV[j]);

    /* the heliocentric coordinates of Mars in AU and AU/day */
    calceph_compute_unit(peph, jd0, dt1, 4, 11,
        CALCEPH_UNIT_AU+CALCEPH_UNIT_DAY,
        PV);
    for(j=0; j<6; j++) printf("%23.16E\n", PV[j]);

    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.7 calceph_orient_unit

int **calceph_orient_unit**(*t_calcephbin* *eph, double JD0, double time, int target, int unit, double PV[6])

Parameters

- **eph** -- ephemeris descriptor
- **JD0** -- Integer part of the Julian date (TDB or TCB)
- **time** -- Fraction part of the Julian date (TDB or TCB)
- **target** -- The body whose orientations are requested. The numbering system depends on the parameter unit.
- **unit** --
The units of PV.
This integer is a sum of some unit constants (CALCEPH_UNIT_???) and/or the constant *CALCEPH_USE_NAIFID*.
If the unit contains *CALCEPH_USE_NAIFID*, the NAIF identification numbering system is used for the target (*NAIF identification numbers* for the list).
If the unit does not contain *CALCEPH_USE_NAIFID*, the old number system is used for the target (see the list in the function *calceph_compute()*).
- **PV** -- An array to receive the euler angles, or nutation angles, and their derivatives for the orientation of the body.

Returns

0 if an error occurs, otherwise non-zero value.

This function reads, if needed, in the ephemeris file associated to *eph* and interpolates the orientation of a single body (*target*) for the time *JD0+time* and stores the results to *PV*. The ephemeris file associated to *eph* must have been previously opened with the function *calceph_open()*. The output values are expressed in the units specified by *unit*.

The date (JD0, time) should be expressed in the same timescale as the ephemeris files, which can be retrieved using the function *calceph_gettimescale()*.

This function checks the units if invalid combinations of units are given to the function.

The returned array *PV* has the following properties

- If *unit* contains `CALCEPH_OUTPUT_NUTATIONANGLES`, the array contains the nutation angles and their derivatives for the orientation of the body. At the present moment, only the nutation for the earth are supported in the original DE files.
- If *unit* contains `CALCEPH_OUTPUT_EULERANGLES`, or doesnot contain `CALCEPH_OUTPUT_NUTATIONANGLES`, the array contains the euler angles and their derivatives for the orientation of the body.

The values stored in the array *PV* are expressed in the following units

- The derivatives of the angles are expressed in days if unit contains `CALCEPH_UNIT_DAY`.
- The derivatives of the angles are expressed in seconds if unit contains `CALCEPH_UNIT_SEC`.
- The angles and their derivatives are expressed in radians if unit contains `CALCEPH_UNIT_RAD`.

For example, to get the nutation angles of the Earth and their derivatives expressed in radian and radian/seconds using the NAIF identification numbering system, the target must be set to `NAIFID_EARTH` and the unit must be set to `CALCEPH_OUTPUT_NUTATIONANGLES + CALCEPH_UNIT_RAD + CALCEPH_UNIT_SEC`.

The following example prints the angles of libration of the Moon at time=2442457.5

```
int j;
double jd0=2442457;
double dt1=0.5E0;
t_calcephbin *peph;
double PV[6];

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    calceph_prefetch(peph);

    calceph_orient_unit(peph, jd0, dt1, NAIFID_MOON,
                       CALCEPH_USE_NAIFID+CALCEPH_UNIT_RAD
                       +CALCEPH_UNIT_SEC,
                       PV);
    for(j=0; j<6; j++) printf("%23.16E\n", PV[j]);

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.8 calceph_rotangmom_unit

int `calceph_rotangmom_unit`(*t_calcephbin* *eph, double JD0, double time, int target, int unit, double PV[6])

Parameters

- **eph** -- ephemeris descriptor
- **JD0** -- Integer part of the Julian date (TDB or TCB)
- **time** -- Fraction part of the Julian date (TDB or TCB)
- **target** -- The body whose orientations are requested. The numbering system depends on the parameter unit.
- **unit** --

The units of PV.

This integer is a sum of some unit constants (CALCEPH_UNIT_???) and/or the constant *CALCEPH_USE_NAIFID*.

If the unit contains *CALCEPH_USE_NAIFID*, the NAIF identification numbering system is used for the target (*NAIF identification numbers* for the list).

If the unit does not contain *CALCEPH_USE_NAIFID*, the old number system is used for the target (see the list in the function *calceph_compute()*).

- **PV** -- An array to receive the angular momentum due to its rotation, divided by the product of the mass and of the square of the radius, and the derivatives, of the body.

Returns

0 if an error occurs, otherwise non-zero value.

This function reads, if needed, in the ephemeris file associated to *eph* and interpolates the angular momentum vector due to the rotation of the body, divided by the product of the mass *m* and of the square of the radius *R*, of a single body (*target*) for the time *JD0+time* and stores the results to *PV*. The ephemeris file associated to *eph* must have been previously opened with the function *calceph_open()*. The angular momentum *L*, due to the rotation of the body, is defined as the product of the inertia matrix *I* by the angular velocity vector ω . So the returned value is $L/(mR^2) = (I\omega)/(mR^2)$

The date (JD0, time) should be expressed in the same timescale as the ephemeris files, which can be retrieved using the function *calceph_gettimescale()*.

The output values are expressed in the units specified by *unit*.

This function checks the units if invalid combinations of units are given to the function.

The values stored in the array *PV* are expressed in the following units

- The angular momentum and its derivative are expressed in days if unit contains *CALCEPH_UNIT_DAY*.
- The angular momentum and its derivative are expressed in seconds if unit contains *CALCEPH_UNIT_SEC*.

The following example prints the angular momentum, due to its rotation, for the Earth at time=2451419.5

```
int j;
double jd0=2451419;
double dt1=0.5E0;
t_calcephbin *peph;
double G[6];

/* open the ephemeris file */
peph = calceph_open("example2_rotangmom.dat");
if (peph)
{
    calceph_prefetch(peph);

    calceph_rotangmom_unit(peph, jd0, dt1, NAIFID_EARTH,
                          CALCEPH_USE_NAIFID+CALCEPH_UNIT_SEC,
                          G);
    for(j=0; j<6; j++) printf("%23.16E\n", G[j]);

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.9 calceph_compute_order

```
int calceph_compute_order(t_calcephbin *eph, double JD0, double time, int target, int center, int unit, int order,
                        double *PVAJ)
```

Parameters

- **eph** -- ephemeris descriptor
- **JD0** -- Integer part of the Julian date (TDB or TCB)
- **time** -- Fraction part of the Julian date (TDB or TCB)
- **target** -- The body or reference point whose coordinates are required. The numbering system depends on the parameter unit.
- **center** -- The origin of the coordinate system. The numbering system depends on the parameter unit.
- **unit** --
The units of PVAJ.
This integer is a sum of some unit constants (CALCEPH_UNIT_???) and/or the constant *CALCEPH_USE_NAIFID*.
If the unit contains *CALCEPH_USE_NAIFID*, the NAIF identification numbering system is used for the target and the center (*NAIF identification numbers* for the list).
If the unit doesnot contain *CALCEPH_USE_NAIFID*, the old number system is used for the target and the center (see the list in the function *calceph_compute()*).
- **order** -- The order of derivatives
 - = 0 , only the position is computed. The first three numbers of PVAJ are valid for the results.
 - = 1 , only the position and velocity are computed. The first six numbers of PVAJ are valid for the results.
 - = 2 , only the position, velocity and acceleration are computed. The first nine numbers of PVAJ are valid for the results.
 - = 3 , the position, velocity and acceleration and jerk are computed. The first twelve numbers of PVAJ are valid for the results.
 If order equals to 1, the behavior of *calceph_compute_order()* is the same as *calceph_compute_unit()*.
- **PVAJ** -- Depending on the target value, an array to receive the cartesian position (x,y,z), the velocity (xdot, ydot, zdot), the acceleration and the jerk, or a time scale transformation value, or the angles of the librations of the Moon and their successive derivatives, or the nutation angles and their successive derivatives.

Returns

0 if an error occurs, otherwise non-zero value.

This function is similar to the function *calceph_compute_unit()*, except that the order of the computed derivatives is specified.

This function reads, if needed, in the ephemeris file associated to *eph* and interpolates a single object, usually the position and their derivatives of one body (*target*) relative to another (*center*) for the time *JD0+time* and stores the results to *PVAJ*. The ephemeris file associated to *eph* must have been previously opened with the function *calceph_open()*. The order of the derivatives are specified by *order*. The output values are expressed in the units specified by *unit*.

The returned array *PVAJ* has the following properties

- If the target is the time scale transformation TT-TDB, only the first elements of each component will get the result.
- If the target is the time scale transformation *TCG-TCB*, only the first elements of each component will get the result.
- If the target is *Librations*, the array contains the angles of the librations of the Moon and their successive derivatives.
- If the target is *Nutations*, the array contains the nutation angles and their successive derivatives.
- Otherwise the returned value is the cartesian position (x,y,z), the velocity (xdot, ydot, zdot), the jerk and the acceleration.

The returned array *PVAJ* must be large enough to store the results. The size of this array must be equal to $3*(order+1)$.

- *PVAJ*[0..2] contain the position (x,y,z) and is always valid.
- *PVAJ*[3..5] contain the velocity (dx/dt,dy/dt,dz/dt) and is only valid if *order* is greater or equal to 1.
- *PVAJ*[6..8] contain the acceleration ($d^2x/dt^2, d^2y/dt^2, d^2z/dt^2$) and is only valid if *order* is greater or equal to 2.
- *PVAJ*[9..11] contain the jerk ($d^3x/dt^3, d^3y/dt^3, d^3z/dt^3$) and is only valid if *order* is equal to 3.

The date (JD0, time) should be expressed in the same timescale as the ephemeris files, which can be retrieved using the function `calceph_gettimescale()`.

 **Warning**

If a date, expressed in the Coordinated Universal Time (UTC), is supplied to this function, a very large erroneous position will be returned.

The values stored in the array *PVAJ* are expressed in the following units

- The position, velocity, acceleration and jerk are expressed in Astronomical Unit (au) if unit contains `CALCEPH_UNIT_AU`.
- The position, velocity, acceleration and jerk are expressed in kilometers if unit contains `CALCEPH_UNIT_KM`.
- The velocity, acceleration, jerk, TT-TDB, TCG-TCB or the derivatives of the angles of the librations of the Moon are expressed in days if unit contains `CALCEPH_UNIT_DAY`.
- The velocity, acceleration, jerk, TT-TDB, TCG-TCB or the derivatives of the angles of the librations of the Moon are expressed in seconds if unit contains `CALCEPH_UNIT_SEC`.
- The angles of the librations of the Moon are expressed in radians if unit contains `CALCEPH_UNIT_RAD`.

For example, to get the positions, velocities, accelerations and jerks expressed in kilometers and kilometers/seconds, the unit must be set to `CALCEPH_UNIT_KM + CALCEPH_UNIT_SEC`.

This function checks the units if invalid combinations of units are given to the function.

The following example prints the heliocentric coordinates of Mars at time=2442457.5

```
int j;
double jd0=2442457;
double dt1=0.5E0;
t_calcephbin *peph;
double PVAJ[12];
double P[3];
```

(continues on next page)

(continued from previous page)

```

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
  /* compute only the heliocentric position of Mars in km */
  calceph_compute_order(peph, jd0, dt1,
                        NAIFID_MARS_BARYCENTER,
                        NAIFID_SUN,
                        CALCEPH_USE_NAIFID+CALCEPH_UNIT_KM
                        +CALCEPH_UNIT_SEC,
                        0, P);
  for(j=0; j<3; j++) printf("%23.16E\n", P[j]);

  /* compute positions, velocities, accelerations and jerks
  of Mars in km and seconds */
  calceph_compute_order(peph, jd0, dt1,
                        NAIFID_MARS_BARYCENTER,
                        NAIFID_SUN,
                        CALCEPH_USE_NAIFID+CALCEPH_UNIT_KM
                        +CALCEPH_UNIT_SEC,
                        3, PVAJ);
  for(j=0; j<12; j++) printf("%23.16E\n", PVAJ[j]);

  /* close the ephemeris file */
  calceph_close(peph);
}

```

4.4.10 calceph_orient_order

```
int calceph_orient_order(t_calcephbin *eph, double JD0, double time, int target, int unit, int order, double
                        *PVAJ)
```

Parameters

- **eph** -- ephemeris descriptor
- **JD0** -- Integer part of the Julian date (TDB or TCB)
- **time** -- Fraction part of the Julian date (TDB or TCB)
- **target** -- The body whose orientations are requested. The numbering system depends on the parameter unit.
- **unit** --
The units of PV.
This integer is a sum of some unit constants (CALCEPH_UNIT_???) and/or the constant *CALCEPH_USE_NAIFID*.
If the unit contains *CALCEPH_USE_NAIFID*, the NAIF identification numbering system is used for the target (*NAIF identification numbers* for the list).
If the unit does not contain *CALCEPH_USE_NAIFID*, the old number system is used for the target (see the list in the function *calceph_compute()*).
- **order** -- The order of derivatives.

- = 0 , only the angles is computed. The first three numbers of PVAJ are valid for the results.
- = 1 , only the angles and the first derivative are computed. The first six numbers of PVAJ are valid for the results.
- = 2 , only the angles and the first and second derivatives are computed. The first nine numbers of PVAJ are valid for the results.
- = 3 , the angles and the first, second and third derivatives are computed. The first twelve numbers of PVAJ are valid for the results.

If order equals to 1, the behavior of `calceph_orient_order()` is the same as `calceph_orient_unit()`.

- **PVAJ** -- An array to receive the euler angles, or nutation angles, and their derivatives for the orientation of the body.

Returns

0 if an error occurs, otherwise non-zero value.

This function is similar to the function `calceph_orient_unit()`, except that the order of the computed derivatives is specified.

This function reads, if needed, in the ephemeris file associated to `eph` and interpolates the orientation of a single body (*target*) for the time `JD0+time` and stores the results to `PVAJ`. The order of the derivatives are specified by `order`. The ephemeris file associated to `eph` must have been previously opened with the function `calceph_open()`. The output values are expressed in the units specified by `unit`.

This function checks the units if invalid combinations of units are given to the function.

The returned array `PVAJ` has the following properties

- If `unit` contains `CALCEPH_OUTPUT_NUTATIONANGLES`, the array contains the nutation angles and their successive derivatives for the orientation of the body. At the present moment, only the nutation for the earth are supported in the original DE files.
- If `unit` contains `CALCEPH_OUTPUT_EULERANGLES`, or doesnot contain `CALCEPH_OUTPUT_NUTATIONANGLES`, the array contains the euler angles and their successive derivatives for the orientation of the body.

The returned array `PVAJ` must be large enough to store the results. The size of this array must be equal to $3*(order+1)$.

- `PVAJ[0..2]` contain the angles and is always valid.
- `PVAJ[3..5]` contain the first derivative and is only valid if `order` is greater or equal to 1.
- `PVAJ[6..8]` contain the second derivative and is only valid if `order` is greater or equal to 2.
- `PVAJ[9..11]` contain the third derivative and is only valid if `order` is equal to 3.

The values stored in the array `PVAJ` are expressed in the following units

- The derivatives of the angles are expressed in days if unit contains `CALCEPH_UNIT_DAY`.
- The derivatives of the angles are expressed in seconds if unit contains `CALCEPH_UNIT_SEC`.
- The angles and their derivatives are expressed in radians if unit contains `CALCEPH_UNIT_RAD`.

The date (JD0, time) should be expressed in the same timescale as the ephemeris files, which can be retrieved using the function `calceph_gettimescale()`.

The following example prints only the angles of libration of the Moon at time=2442457.5

```
int res;
int j;
double jd0=2442457;
```

(continues on next page)

(continued from previous page)

```

double dt1=0.5E0;
t_calcephbin *peph;
double P[3];

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    calceph_prefetch(peph);

    calceph_orient_order(peph, jd0, dt1, NAIFID_MOON,
        CALCEPH_USE_NAIFID+CALCEPH_UNIT_RAD+CALCEPH_UNIT_SEC,
        0,
        P);
    for(j=0; j<3; j++) printf("%23.16E\n", P[j]);

    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.11 calceph_rotangmom_order

```
int calceph_rotangmom_order(t_calcephbin *eph, double JD0, double time, int target, int unit, int order, double *PVAJ)
```

Parameters

- **eph** -- ephemeris descriptor
- **JD0** -- Integer part of the Julian date (TDB or TCB)
- **time** -- Fraction part of the Julian date (TDB or TCB)
- **target** -- The body whose orientations are requested. The numbering system depends on the parameter unit.
- **unit** --
The units of PV.
This integer is a sum of some unit constants (CALCEPH_UNIT_???) and/or the constant *CALCEPH_USE_NAIFID*.
If the unit contains *CALCEPH_USE_NAIFID*, the NAIF identification numbering system is used for the target (*NAIF identification numbers* for the list).
If the unit does not contain *CALCEPH_USE_NAIFID*, the old number system is used for the target (see the list in the function *calceph_compute()*).
- **order** -- The order of derivatives.
 - = 0 , only the angular momentum is computed. The first three numbers of PVAJ are valid for the results.
 - = 1 , only the angular momentum and the first derivative are computed. The first six numbers of PVAJ are valid for the results.
 - = 2 , only the angular momentum and the first and second derivatives are computed. The first nine numbers of PVAJ are valid for the results.

– = 3 , the angular momentum and the first, second and third derivatives are computed. The first twelve numbers of *PVAJ* are valid for the results.

If *order* equals to 1, the behavior of *calceph_rotangmom_order()* is the same as *calceph_rotangmom_unit()*.

- **PVAJ** -- An array to receive the angular momentum due to its rotation, divided by the product of the mass and of the square of the radius, and their different order of the derivatives, of the body.

Returns

0 if an error occurs, otherwise non-zero value.

This function is similar to the function *calceph_orient_unit()*, except that the order of the computed derivatives is specified.

This function reads, if needed, in the ephemeris file associated to *eph* and interpolates the angular momentum vector due to the rotation of the body, divided by the product of the mass *m* and of the square of the radius *R*, of a single body (*target*) for the time *JD0+time* and stores the results to *PVAJ*. The angular momentum *L* , due to the rotation of the body, is defined as the product of the inertia matrix *I* by the angular velocity vector ω . So the returned value is $L/(mR^2) = (I\omega)/(mR^2)$ The order of the derivatives are specified by *order*. The ephemeris file associated to *eph* must have been previously opened with the function *calceph_open()*. The output values are expressed in the units specified by *unit*.

This function checks the units if invalid combinations of units are given to the function.

The returned array *PVAJ* must be large enough to store the results. The size of this array must be equal to 3*(order+1).

- *PVAJ*[0..2] contain the angular momentum and is always valid.
- *PVAJ*[3..5] contain the first derivative and is only valid if *order* is greater or equal to 1.
- *PVAJ*[6..8] contain the second derivative and is only valid if *order* is greater or equal to 2.
- *PVAJ*[9..11] contain the third derivative and is only valid if *order* is equal to 3.

The values stored in the array *PVAJ* are expressed in the following units

- The angular momentum and its derivatives are expressed in days if *unit* contains *CALCEPH_UNIT_DAY*.
- The angular momentum and its derivatives are expressed in seconds if *unit* contains *CALCEPH_UNIT_SEC*.

The date (JD0, time) should be expressed in the same timescale as the ephemeris files, which can be retrieved using the function *calceph_gettimescale()*.

The following example prints only the angular momentum, due to its rotation, of the Earth at time=2451419.5

```
int j;
double jd0=2451419;
double dt1=0.5E0;
t_calcephbin *peph;
double G[3];

/* open the ephemeris file */
peph = calceph_open("example2_rotangmom.dat");
if (peph)
{
    calceph_prefetch(peph);

    calceph_rotangmom_order(peph, jd0, dt1, NAIFID_EARTH,
        CALCEPH_USE_NAIFID+CALCEPH_UNIT_SEC,
```

(continues on next page)

(continued from previous page)

```

    0,
    G);
for(j=0; j<3; j++) printf("%23.16E\n", G[j]);

/* close the ephemeris file */
calceph_close(peph);
}

```

4.4.12 calceph_getconstant

int **calceph_getconstant**(*t_calcephbin* *eph, const char *name, double *value)

Parameters

- **eph** -- ephemeris descriptor
- **name** -- name of the constant
- **value** -- first value of the constant

Returns

returns 0 if an error occurs, otherwise the number of values associated to the constant.

This function returns the value associated to the constant *name* in the header of the ephemeris file associated to *eph*. Only the first value is returned if multiple values are associated to a constant, such as a list of values.

This function is the same function as *calceph_getconstantsd()*.

The following example prints the value of the astronomical unit stored in the ephemeris file

```

double AU;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* print the value of AU */
    if (calceph_getconstant(peph, "AU", &AU))
        printf("AU=%23.16E\n", AU);

    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.13 calceph_getconstantsd

int **calceph_getconstantsd**(*t_calcephbin* *eph, const char *name, double *value)

Parameters

- **eph** -- ephemeris descriptor
- **name** -- name of the constant
- **value** -- first value of the constant

Returns

returns 0 if an error occurs, otherwise the number of values associated to the constant.

This function returns, as a floating-point number, the value associated to the constant *name* in the header of the ephemeris file associated to *eph*. Only the first value is returned if multiple values are associated to a constant, such as a list of values. The value must be a floating-point or integer number, otherwise an error is reported.

This function is the same function as `calceph_getconstant()`.

The following example prints the value of the astronomical unit stored in the ephemeris file

```
double AU;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* print the value of AU */
    if (calceph_getconstantsd(peph, "AU", &AU))
        printf("AU=%23.16E\n", AU);

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.14 calceph_getconstantvd

int `calceph_getconstantvd(t_calcephbin *eph, const char *name, double *arrayvalue, int nvalue)`

Parameters

- **eph** -- ephemeris descriptor
- **name** -- name of the constant
- **arrayvalue** -- array of values for the constant
- **nvalue** -- number of elements of the array

Returns

returns 0 if an error occurs, otherwise the number of values associated to the constant.

This function stores, to the array *arrayvalue* as floating-point numbers, the *nvalue* first values associated to the constant *name* in the header of the ephemeris file associated to *eph*. The integer value returned by the function is equal to the number of valid entries in the *arrayvalue* if *nvalue* is greater or equal to that integer value..

The required value *nvalue* to store all values can be determined with this previous call `calceph_getconstantvd(eph, name, NULL, 0)`.

The values must be floating-point or integer numbers, otherwise an error is reported.

The following example prints the body radii of the earth stored in the ephemeris file

```
int nvalue, k;
double *radii;
t_calcephbin *peph;

/* open the ephemeris file */
```

(continues on next page)

(continued from previous page)

```

peph = calceph_open("example1.dat");
if (peph)
{
    /* get the number of values */
    int nvalue = calceph_getconstantvd(peph, "BODY399_RADII", NULL, 0);
    radii = (double*)malloc(sizeof(double)*nvalue);

    /* fill the array radii */
    if (calceph_getconstantvd(peph, "BODY399_RADII", radii, nvalue))
    {
        for (k=0; k<nvalue; k++)
            printf("BODY399_RADII(%d)=%23.16E\n", k, radii[k]);
    }
    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.15 calceph_getconstantss

int **calceph_getconstantss**(*t_calcephbin* *eph, const char *name, *t_calcephcharvalue* value)

Parameters

- **eph** -- ephemeris descriptor
- **name** -- name of the constant
- **value** -- first value of the constant

Returns

returns 0 if an error occurs, otherwise the number of values associated to the constant.

This function returns, as a string of character, the value associated to the constant *name* in the header of the ephemeris file associated to *eph*. Only the first value is returned if multiple values are associated to a constant, such as a list of values. The value must be a string, otherwise an error is reported.

The following example prints the value of the unit stored in the ephemeris file

```

t_calcephcharvalue unit;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* print the value of UNIT */
    if (calceph_getconstantss(peph, "UNIT", unit))
        printf("UNIT=%s\n", unit);

    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.16 calceph_getconstantvs

int **calceph_getconstantvs**(*t_calcephbin* *eph, const char *name, *t_calcephcharvalue* *arrayvalue, int nvalue)

Parameters

- **eph** -- ephemeris descriptor
- **name** -- name of the constant
- **arrayvalue** -- array of values for the constant
- **nvalue** -- number of elements of the array

Returns

returns 0 if an error occurs, otherwise the number of values associated to the constant.

This function stores, to the array *arrayvalue* as strings of characters, the *nvalue* first values associated to the constant *name* in the header of the ephemeris file associated to *eph*. The integer value returned by the function is equal to the number of valid entries in the *arrayvalue* if *nvalue* is greater or equal to that integer value.

The required value *nvalue* to store all values can be determined with this previous call *calceph_getconstantvs(eph, name, NULL, 0)*.

The values must be strings, otherwise an error is reported.

The following example prints the units of the mission stored in the ephemeris file

```
int nvalue, k;
t_calcephcharvalue *mission_units;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* get the number of values */
    int nvalue = calceph_getconstantvs(peph, "MISSION_UNITS", NULL, 0);
    mission_units = (t_calcephcharvalue*)malloc(sizeof(t_calcephcharvalue)*nvalue);

    /* fill the array radii */
    if (calceph_getconstantvs(peph, "MISSION_UNITS", mission_units, nvalue))
    {
        for (k=0; k<nvalue; k++)
            printf("MISSION_UNITS(%d)=%s\n", k, mission_units[k]);
    }
    free(mission_units);
    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.17 calceph_getconstantcount

int **calceph_getconstantcount**(*t_calcephbin* *eph)

Parameters

- **eph** -- ephemeris descriptor

Returns

number of constants. 0 if an error occurs, otherwise non-zero value.

This function returns the number of constants available in the header of the ephemeris file associated to *eph*.

The following example prints the number of available constants stored in the ephemeris file

```
int count;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* print the number of constants */
    count = calceph_getconstantcount(peph);
    printf("number of constants : %d\n", count);

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.18 calceph_getconstantindex

```
int calceph_getconstantindex(t_calcephbin *eph, int index, char name[CALCEPH_MAX_CONSTANTNAME],
double *value)
```

Parameters

- **eph** -- ephemeris descriptor
- **index** -- index of the constant, between 1 and *calceph_getconstantcount()*
- **name** -- name of the constant
- **value** -- first value of the constant

Returns

returns 0 if an error occurs, otherwise the number of values associated to the constant.

This function returns the name and its value of the constant available at the specified index in the header of the ephemeris file associated to *eph*. The value of *index* must be between 1 and *calceph_getconstantcount()*.

Only the first value is returned if multiple values are associated to a constant, such as a list of values. If the first value is not an floating-point number, such as a string, then the function returns 0 without raising an error.

The following example displays the name of the constants, stored in the ephemeris file, and their values

```
int j;
char nameconstant[CALCEPH_MAX_CONSTANTNAME];
double valueconstant;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    for (j=1; j<=calceph_getconstantcount(peph); j++)
```

(continues on next page)

(continued from previous page)

```

{
    calceph_getconstantindex(peph, j, nameconstant, &valueconstant);
    printf("%s\t= %23.16E\n", nameconstant, valueconstant);
}

/* close the ephemeris file */
calceph_close(peph);
}

```

4.4.19 calceph_getfileversion

int **calceph_getfileversion**(*t_calcephbin* *eph, char version[*CALCEPH_MAX_CONSTANTVALUE*])

Parameters

- **eph** -- ephemeris descriptor
- **version** -- version of the file

Returns

returns 0 if the file version was not found, otherwise non-zero value.

This function returns the version of the ephemeris file, as a string. For example, the argument version will contain 'INPOP10B', 'EPM2017' or 'DE405',

If the file is an original JPL binary planetary ephemeris, then the version of the file can always be determined. If the file is a spice kernel, the version of the file is retrieved from the constant *INPOP_PCK_VERSION*, *EPM_PCK_VERSION*, or *PCK_VERSION*.

The following example prints the version of the ephemeris file.

```

char version[CALCEPH_MAX_CONSTANTVALUE];
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    if (calceph_getfileversion(peph, version))
        printf("The version of the file is %s\n", version);

    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.20 calceph_getidbyname

int **calceph_getidbyname**(*t_calcephbin* *eph, const char *name, int unit, int *id)

Parameters

- **eph** -- ephemeris descriptor
- **name** -- name of the body
- **unit** --
The unit of id.

This integer is 0 or the constant `CALCEPH_USE_NAIFID`.

If the unit equals `CALCEPH_USE_NAIFID`, the NAIF identification numbering system is used for the id (*NAIF identification numbers* for the list).

If the unit equals 0, the old number system is used for the idr (see the list in the function `calceph_compute()`).

- **id** -- id of the body. The numbering system depends on the parameter unit.

Returns

returns 0 if the name of the body was not found, otherwise non-zero value.

This function returns, in the parameter *id*, the identification number of the body associated to the given name.

The function is not sensitive to the case of the characters of the string *name*. Leading and trailing spaces are ignored. At least one space character is required between the words. For example, 'Saturn Barycenter' is the same as ' Saturn Barycenter ', but is different from 'SaturnBarycenter'.

The library has a default mapping listed in the list *NAIF identification numbers*. The mapping name/id may be overridden by the text constants `NAIF_BODY_CODE` and `NAIF_BODY_NAME` in the 'SPICE' ephemeris files.

The following example prints the identification number of the Moon.

```
int moon;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* print the id of the Moon using the old numbering system */
    if (calceph_getidbyname(peph, "Moon", 0, &moon))
        printf("Moon=%d\n", moon);
    /* print the id of the Moon using the NAIF identification numbering system */
    if (calceph_getidbyname(peph, "Moon", CALCEPH_USE_NAIFID, &moon))
        printf("Moon=%d\n", moon);

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.21 calceph_getnamebyidss

```
int calceph_getnamebyidss(t_calcephbin *eph, int id, int unit, char
                        name[CALCEPH_MAX_CONSTANTVALUE])
```

Parameters

- **eph** -- ephemeris descriptor
- **name** -- name of the body
- **unit** --

The unit of id.

This integer is 0 or the constant `CALCEPH_USE_NAIFID`.

If the unit equals `CALCEPH_USE_NAIFID`, the NAIF identification numbering system is used for the id (*NAIF identification numbers* for the list).

If the unit equals 0, the old number system is used for the *idr* (see the list in the function *calceph_compute()*).

- **id** -- id of the body. The numbering system depends on the parameter unit.

Returns

returns 0 if the name of the body was not found, otherwise non-zero value.

This function returns, in the parameter *name*, the first given name of the body associated to the identification number *id*.

The library has a default mapping listed in the list *NAIF identification numbers*. The mapping name/id may be overridden by the text constants *NAIF_BODY_CODE* and *NAIF_BODY_NAME* in the 'SPICE' ephemeris files.

The following example prints the name of the Earth-Moon barycenter.

```
t_calcephcharvalue emb;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* print the name of the Earth-Moon barycenter using the old numbering system */
    if (calceph_getnamebyidss(peph, 13, 0, &emb))
        printf("EMB=%d\n", emb);
    /* print the name of the Earth-Moon barycenter using the NAIF identification_
    ↪ numbering system */
    if (calceph_getidbyname(peph, 3, CALCEPH_USE_NAIFID, &emb))
        printf("EMB=%d\n", emb);

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.22 calceph_gettimescale

int **calceph_gettimescale**(*t_calcephbin* *eph)

Parameters

- **eph** -- ephemeris descriptor

Returns

0 if an error occurs, otherwise non-zero value.

This function returns the timescale of the ephemeris file associated to *eph* :

- 1 if the quantities of all bodies are expressed in the TDB time scale.
- 2 if the quantities of all bodies are expressed in the TCB time scale.

The following example prints the time scale available in the ephemeris file

```
t_calcephbin *peph;
int timescale;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
```

(continues on next page)

(continued from previous page)

```

if (peph)
{
    /* print the time scale */
    timescale = calceph_gettimescale(peph);
    if (timescale==1) printf("timescale=TDB\n");
    if (timescale==2) printf("timescale=TCB\n");

    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.23 calceph_gettimespan

`int calceph_gettimespan(t_calcephbin *eph, double *firsttime, double *lasttime, int *continuous)`

Parameters

- **eph** -- ephemeris descriptor
- **firsttime** -- Julian date of the first time
- **lasttime** -- Julian date of the last time
- **continuous** -- information about the availability of the quantities over the time span

Returns

0 if an error occurs, otherwise non-zero value.

This function returns the first and last time available in the ephemeris file associated to *eph*. The Julian date for the first and last time are expressed in the time scale returned by *calceph_gettimescale()*.

It returns the following value in the parameter *continuous* :

- 1 if the quantities of all bodies are available for any time between the first and last time.
- 2 if the quantities of some bodies are available on discontinuous time intervals between the first and last time.
- 3 if the quantities of each body are available on a continuous time interval between the first and last time, but not available for any time between the first and last time.

The following example prints the first and last time available in the ephemeris file

```

double firsttime, lasttime;
int countinuous;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    if (calceph_gettimespan(peph, &firsttime, &lasttime, &countinuous))
        printf("%23.16E %23.16E %d\n", firsttime, lasttime, countinuous);

    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.24 calceph_getpositionrecordcount

int **calceph_getpositionrecordcount**(*t_calcephbin* *eph)

Parameters

- **eph** -- ephemeris descriptor

Returns

number of position's records. 0 if an error occurs, otherwise non-zero value.

This function returns the number of position's records available in the ephemeris file associated to *eph*. Usually, the number of records is equal to the number of bodies in the ephemeris file if the timespan is continuous. If the timespan is discontinuous for the target and center bodies, then each different timespan is counted as a different record. If the ephemeris file contain timescale transformations' records, such as *TT-TDB* or *TCG-TCB*, then these records are included in the returned value.

The following example prints the number of position's records available in the ephemeris file

```
int count;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* print the number of position's record */
    count = calceph_getpositionrecordcount(peph);
    printf("number of position's record : %d\n", count);

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.25 calceph_getpositionrecordindex

int **calceph_getpositionrecordindex**(*t_calcephbin* *eph, int index, int *target, int *center, double *firsttime, double *lasttime, int *frame)

Parameters

- **eph** -- ephemeris descriptor
- **index** -- index of the position's record, between 1 and *calceph_getpositionrecordcount()*
- **target** -- The target body
- **center** -- The origin body
- **firsttime** -- Julian date of the first time
- **lasttime** -- Julian date of the last time
- **frame** -- reference frame (see the list, below)

Returns

0 if an error occurs, otherwise non-zero value.

This function returns the target and origin bodies, the first and last time, and the reference frame available at the specified index for the position's records of the ephemeris file associated to *eph*. The NAIF identification numbering system is

used for the target and center integers (*NAIF identification numbers* for the list). The Julian date for the first and last time are expressed in the time scale returned by `calceph_gettimescale()`.

It returns the following value in the parameter *frame* :

value	Name
1	ICRF

The following example displays the position's records stored in the ephemeris file.

```
int j;
int res;
double firsttime, lasttime;
int itarget, icenter, iframe;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    for (j=1; j<=calceph_getpositionrecordcount(peph); j++)
    {
        calceph_getpositionrecordindex(peph, j, &itarget, &icenter, &firsttime, &lasttime,
        ↪ &iframe);
        printf("record %d : target=%d center=%d start=%23.16E end=%23.16E frame=%d\n",
            j, itarget, icenter, firsttime, lasttime, iframe);
    }

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.26 calceph_getpositionrecordindex2

int `calceph_getpositionrecordindex2`(*t_calcephbin* *eph, int index, int *target, int *center, double *firsttime, double *lasttime, int *frame, int *segid)

Parameters

- **eph** -- ephemeris descriptor
- **index** -- index of the position's record, between 1 and `calceph_getpositionrecordcount()`
- **target** -- The target body
- **center** -- The origin body
- **firsttime** -- Julian date of the first time
- **lasttime** -- Julian date of the last time
- **frame** -- reference frame (see the list, below)
- **segid** -- type of the segment.

Returns

0 if an error occurs, otherwise non-zero value.

This function returns the target and origin bodies, the first and last time, the reference frame, and the segment type available at the specified index for the position's records of the ephemeris file associated to *eph*. The NAIF identification numbering system is used for the target and center integers (*NAIF identification numbers* for the list). The Julian date for the first and last time are expressed in the time scale returned by *calceph_gettimescale()*.

It returns the following value in the parameter *frame* :

value	Name
1	ICRF

It returns in the parameter *segid* one of the predefined constants *CALCEPH_SEGTYPE_...* (*Constants*).

The following example displays the position's records stored in the ephemeris file.

```
int j;
double firsttime, lasttime;
int itarget, icenter, iframe, segtype;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    for (j=1; j<=calceph_getpositionrecordcount(peph); j++)
    {
        calceph_getpositionrecordindex2(peph, j, &itarget, &icenter, &firsttime, &
↪lasttime, &iframe, &segtype);
        printf("record %d : target=%d center=%d start=%23.16E end=%23.16E frame=%d_
↪segtype=%d\n",
            j, itarget, icenter, firsttime, lasttime, iframe, segtype);
    }

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.27 calceph_getorientrecordcount

int *calceph_getorientrecordcount*(*t_calcephbin* *eph)

Parameters

- **eph** -- ephemeris descriptor

Returns

number of orientation's records. 0 if an error occurs, otherwise non-zero value.

This function returns the number of orientation's records available in the ephemeris file associated to *eph*. Usually, the number of records is equal to the number of bodies in the ephemeris file if the timespan is continuous. If the timespan is discontinuous for the target body, then each different timespan is counted as a different record.

The following example prints the number of orientation's records available in the ephemeris file

```
int count;
t_calcephbin *peph;
```

(continues on next page)

(continued from previous page)

```

/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    /* print the number of orientation's record */
    count = calceph_getorientrecordcount(peph);
    printf("number of orientation's record : %d\n", count);

    /* close the ephemeris file */
    calceph_close(peph);
}

```

4.4.28 calceph_getorientrecordindex

```
int calceph_getorientrecordindex(t_calcephbin *eph, int index, int *target, double *firsttime, double
                                *lasttime, int *frame)
```

Parameters

- **eph** -- ephemeris descriptor
- **index** -- index of the orientation's record, between 1 and `calceph_getorientrecordcount()`
- **target** -- The target body
- **firsttime** -- Julian date of the first time
- **lasttime** -- Julian date of the last time
- **frame** -- reference frame (see the list, below)

Returns

0 if an error occurs, otherwise non-zero value.

This function returns the target body, the first and last time, and the reference frame available at the specified index for the orientation's records of the ephemeris file associated to *eph*. The NAIF identification numbering system is used for the target body (*NAIF identification numbers* for the list). The Julian date for the first and last time are expressed in the time scale returned by `calceph_gettimescale()`.

It returns the following value in the parameter *frame* :

value	Name
1	ICRF

The following example displays the orientation's records stored in the ephemeris file.

```

int j;
double firsttime, lasttime;
int itarget, iframe;
t_calcephbin *peph;

/* open the ephemeris file */
peph = calceph_open("example1.dat");

```

(continues on next page)

(continued from previous page)

```

if (peph)
{
  for (j=1; j<=calceph_getorientrecordcount(peph); j++)
  {
    calceph_getorientrecordindex(peph, j, &itarget, &firsttime, &lasttime, &iframe);
    printf("record %d : target=%d start=%23.16E end=%23.16E frame=%d\n",
          j, itarget, firsttime, lasttime, iframe);
  }

  /* close the ephemeris file */
  calceph_close(peph);
}

```

4.4.29 calceph_getorientrecordindex2

```

int calceph_getorientrecordindex2(t_calcephbin *eph, int index, int *target, double *firsttime, double
                                *lasttime, int *frame, int *segid)

```

Parameters

- **eph** -- ephemeris descriptor
- **index** -- index of the orientation's record, between 1 and `calceph_getorientrecordcount()`
- **target** -- The target body
- **firsttime** -- Julian date of the first time
- **lasttime** -- Julian date of the last time
- **frame** -- reference frame (see the list, below)
- **segid** -- type of the segment.

Returns

0 if an error occurs, otherwise non-zero value.

This function returns the target body, the first and last time, the reference frame and the segment type available at the specified index for the orientation's records of the ephemeris file associated to *eph*. The NAIF identification numbering system is used for the target body (*NAIF identification numbers* for the list). The Julian date for the first and last time are expressed in the time scale returned by `calceph_gettimescale()`.

It returns the following value in the parameter *frame* :

value	Name
1	ICRF

It returns in the parameter *segid* one of the predefined constants `CALCEPH_SEGTYPE_...` (*Constants*).

The following example displays the orientation's records stored in the ephemeris file.

```

int j;
double firsttime, lasttime;
int itarget, iframe, iseg;
t_calcephbin *peph;

```

(continues on next page)

(continued from previous page)

```
/* open the ephemeris file */
peph = calceph_open("example1.dat");
if (peph)
{
    for (j=1; j<=calceph_getorientrecordcount(peph); j++)
    {
        calceph_getorientrecordindex2(peph, j, &itarget, &firsttime, &lasttime, &iframe, &
↪iseg);
        printf("record %d : target=%d start=%23.16E end=%23.16E frame=%d segtype=%d\n",
                j, itarget, firsttime, lasttime, iframe, iseg);
    }

    /* close the ephemeris file */
    calceph_close(peph);
}
```

4.4.30 calceph_close

void **calceph_close**(*t_calcephbin* *eph)

Parameters

- **eph** -- ephemeris descriptor

This function closes the access associated to the ephemeris descriptor *eph* and frees allocated memory for it.

ERROR FUNCTIONS

The following group of functions defines the behavior of the library when errors occur during the execution.

5.1 Usage

The following examples, that can be found in the directory *examples* of the library sources, show the typical usage of this group of functions.

The example in C language is `cerror.c`.

The following example shows how to stop the execution on the error.

```
t_calcephbin * eph;

/* set the error handler to stop on error */
calceph_seterrorhandler(2, 0);

/* open the ephemeris file */
eph = calceph_open("example1.dat");

/*... computation ... */
```

The following example shows how to define a custom error handler function.

```
/*-----*/
/* custom error handler */
/*-----*/
static void myhandler(const char *msg)
{
    puts("The calceph calls the function myhandler");
    printf("The message contains %d characters\n", (int)strlen(msg));
    puts("The error message is :");
    puts("-----");
    puts(msg);
    puts("-----");
    puts("The error handler returns");
}

int main(void)
{
    t_calcephbin * eph;
```

(continues on next page)

(continued from previous page)

```

/* set the error handler to stop on error */
calceph_seterrorhandler(3, myhandler);

/* open the ephemeris file */
eph = calceph_open("example1.dat");

/*... computation ... */

return 0;
}

```

5.2 calceph_seterrorhandler

void **calceph_seterrorhandler**(int typehandler, void (*userfunc)(const char*))

Parameters

- **typehandler** -- type of handler
- **userfunc** -- user function

This function defines the behavior of the library when an error occurs during the execution of the library's functions. This function should be (not mandatory) called before any other functions of the library. The behavior depends on the value of *typehandler*.

The possible values for *typehandler* are :

value	meaning
1	The library displays a message and continues the execution. The functions return an error code. The python and Octave/Matlab interfaces raise an exception. This is the default behavior of the library.
2	The library displays a message and terminates the execution with a system call to the function <i>exit</i> .
3	The library calls the user function <i>userfunc</i> with the message.

If the function is called with 1 or 2 for *typehandler*, the parameter *userfunc* must be set to *NULL*.

MISCELLANEOUS FUNCTIONS

6.1 `calceph_getmaxsupportedorder`

int `calceph_getmaxsupportedorder`(int `segid`)

Parameters

- `segid` -- type of the segment.

Returns

maximal order of the computable derivatives for this type of segment.

This function returns the maximal order of the derivatives computed by the functions `calceph_compute_order()`, `calceph_orient_order()`, for the segment type `segid`. If the segment type is unknown by the library, the function returns -1.

The accepted values of `segid` are the predefined constants `CALCEPH_SEGTYPE_...` (*Constants*).

```
int maxorder = calceph_getmaxsupportedorder(CALCEPH_SEGTYPE_SPK_2);
printf ("maximal order is %d \n", maxorder);
```

6.2 `calceph_getversion_str`

void `calceph_getversion_str`(char `version`[`CALCEPH_MAX_CONSTANTNAME`])

Parameters

- `version` -- version of the library

This function returns the version of the CALCEPH Library, as a null-terminated string.

```
char cversion[CALCEPH_MAX_CONSTANTNAME];
calceph_getversion_str(cversion);
printf ("library version is '%s'\n", cversion);
```


NAIF IDENTIFICATION NUMBERS

The following predefined values must be used as the target body and origin of the coordinate system with the functions `calceph_compute_unit()`, `calceph_orient_unit()`, `calceph_compute_order()` or `calceph_orient_order()` if and only if the value `CALCEPH_USE_NAIFID` has been set in the parameter `unit`.

This list is already predefined in the interface file `calceph.h`.

7.1 Sun and planetary barycenters

Predefined Macros	NAIF ID	Name
<code>NAIFID_SOLAR_SYSTEM_BARYCENTER</code>	0	Solar System Barycenter
<code>NAIFID_MERCURY_BARYCENTER</code>	1	Mercury Barycenter
<code>NAIFID_VENUS_BARYCENTER</code>	2	Venus Barycenter
<code>NAIFID_EARTH_MOON_BARYCENTER</code>	3	Earth-Moon Barycenter
<code>NAIFID_MARS_BARYCENTER</code>	4	Mars Barycenter
<code>NAIFID_JUPITER_BARYCENTER</code>	5	Jupiter Barycenter
<code>NAIFID_SATURN_BARYCENTER</code>	6	Saturn Barycenter
<code>NAIFID_URANUS_BARYCENTER</code>	7	Uranus Barycenter
<code>NAIFID_NEPTUNE_BARYCENTER</code>	8	Neptune Barycenter
<code>NAIFID_PLUTO_BARYCENTER</code>	9	Pluto Barycenter
<code>NAIFID_SUN</code>	10	Sun

7.2 Coordinate Time ephemerides

Predefined Macros	NAIF ID	Name
<code>NAIFID_TIME_CENTER</code>	1000000000	center ID for Coordinate Time ephemerides ¹
<code>NAIFID_TIME_TTMTDB</code>	1000000001	Coordinate Time ephemeride TT-TDB ²
<code>NAIFID_TIME_TCGMTCB</code>	1000000002	Coordinate Time ephemeride TCG-TCB ²

7.3 Planet centers and satellites

¹ These values must only be used as a center body.

² These values must only be used as a target body.

Predefined Macros	NAIF ID	Name
NAIFID_MERCURY	199	Mercury
NAIFID_VENUS	299	Venus
NAIFID_EARTH	399	Earth
NAIFID_MOON	301	Moon
NAIFID_MARS	499	Mars
NAIFID_PHOBOS	401	Phobos
NAIFID_DEIMOS	402	Deimos
NAIFID_JUPITER	599	Jupiter
NAIFID_IO	501	Io
NAIFID_EUROPA	502	Europa
NAIFID_GANYMEDE	503	Ganymede
NAIFID_CALLISTO	504	Callisto
NAIFID_AMALTHEA	505	Amalthea
NAIFID_HIMALIA	506	Himalia
NAIFID_ELARA	507	Elara
NAIFID_PASIPHAE	508	Pasiphae
NAIFID_SINOPE	509	Sinope
NAIFID_LYSITHEA	510	Lysithea
NAIFID_CARME	511	Carme
NAIFID_ANANKE	512	Ananke
NAIFID_LEDA	513	Leda
NAIFID_THEBE	514	Thebe
NAIFID_ADRASTEIA	515	Adrastea
NAIFID_METIS	516	Metis
NAIFID_CALLIRRHOE	517	Callirrhoe
NAIFID_THEMISTO	518	Themisto
NAIFID_MEGACLITE	519	Megaclite
NAIFID_TAYGETE	520	Taygete
NAIFID_CHALDENE	521	Chaldene
NAIFID_HARPALYKE	522	Harpalyke
NAIFID_KALYKE	523	Kalyke
NAIFID_IOCASTE	524	Iocaste
NAIFID_ERINOME	525	Erinome
NAIFID_ISONOE	526	Isonoe
NAIFID_PRAXIDIKE	527	Praxidike
NAIFID_AUTONOE	528	Autonoe
NAIFID_THYONE	529	Thyone
NAIFID_HERMIPPE	530	Hermippe
NAIFID_AITNE	531	Aitne
NAIFID_EURYDOME	532	Eurydome
NAIFID_EUANTHE	533	Euanthe
NAIFID_EUPORIE	534	Euporie
NAIFID_ORTHOSIE	535	Orthosie
NAIFID_SPONDE	536	Sponde
NAIFID_KALE	537	Kale
NAIFID_PASITHEE	538	Pasithee
NAIFID_HEGEMONE	539	Hegemone

continues on next page

Table 1 – continued from previous page

Predefined Macros	NAIF ID	Name
NAIFID_MNEME	540	Mneme
NAIFID_AOEDE	541	Aoede
NAIFID_THELXINOE	542	Thelxinoe
NAIFID_ARCHE	543	Arche
NAIFID_KALLICHORE	544	Kallichore
NAIFID_HELIKE	545	Helike
NAIFID_CARPO	546	Carpo
NAIFID_EUKELADE	547	Eukelade
NAIFID_CYLLENE	548	Cyllene
NAIFID_KORE	549	Kore
NAIFID_HERSE	550	Herse
NAIFID_DIA	553	Dia
NAIFID_SATURN	699	Saturn
NAIFID_MIMAS	601	Mimas
NAIFID_ENCELADUS	602	Enceladus
NAIFID_TETHYS	603	Tethys
NAIFID_DIONE	604	Dione
NAIFID_RHEA	605	Rhea
NAIFID_TITAN	606	Titan
NAIFID_HYPERION	607	Hyperion
NAIFID_IAPETUS	608	Iapetus
NAIFID_PHOEBE	609	Phoebe
NAIFID_JANUS	610	Janus
NAIFID_EPIMETHEUS	611	Epimetheus
NAIFID_HELENE	612	Helene
NAIFID_TELESTO	613	Telesto
NAIFID_CALYPSO	614	Calypso
NAIFID_ATLAS	615	Atlas
NAIFID_PROMETHEUS	616	Prometheus
NAIFID_PANDORA	617	Pandora
NAIFID_PAN	618	Pan
NAIFID_YMIR	619	Ymir
NAIFID_PAALIAQ	620	Paaliaq
NAIFID_TARVOS	621	Tarvos
NAIFID_IJIRAQ	622	Ijiraq
NAIFID_SUTTUNGR	623	Suttungr
NAIFID_KIVIUQ	624	Kiviuq
NAIFID_MUNDILFARI	625	Mundilfari
NAIFID_ALBIORIX	626	Albiorix
NAIFID_SKATHI	627	Skathi
NAIFID_ERRIAPUS	628	Erriapus
NAIFID_SIARNAQ	629	Siarnaq
NAIFID_THRYMR	630	Thrymr
NAIFID_NARVI	631	Narvi
NAIFID_METHONE	632	Methone
NAIFID_PALLENE	633	Pallene
NAIFID_POLYDEUCES	634	Polydeuces
NAIFID_DAPHNIS	635	Daphnis
NAIFID_AEGIR	636	Aegir

continues on next page

Table 1 – continued from previous page

Predefined Macros	NAIF ID	Name
NAIFID_BEBHIONN	637	Bebhionn
NAIFID_BERGELMIR	638	Bergelmir
NAIFID_BESTLA	639	Bestla
NAIFID_FARBAUTI	640	Farbauti
NAIFID_FENRIR	641	Fenrir
NAIFID_FORNJOT	642	Fornjot
NAIFID_HATI	643	Hati
NAIFID_HYROKKIN	644	Hyrokkin
NAIFID_KARI	645	Kari
NAIFID_LOGE	646	Loge
NAIFID_SKOLL	647	Skoll
NAIFID_SURTUR	648	Surtur
NAIFID_ANTHE	649	Anthe
NAIFID_JARNSAXA	650	Jarnsaxa
NAIFID_GREIP	651	Greip
NAIFID_TARQEQ	652	Tarqeq
NAIFID_AEGAEON	653	Aegaeon
NAIFID_URANUS	799	Uranus
NAIFID_ARIEL	701	Ariel
NAIFID_UMBRIEL	702	Umbriel
NAIFID_TITANIA	703	Titania
NAIFID_OBERON	704	Oberon
NAIFID_MIRANDA	705	Miranda
NAIFID_CORDELIA	706	Cordelia
NAIFID_OPHELIA	707	Ophelia
NAIFID_BIANCA	708	Bianca
NAIFID_CRESSIDA	709	Cressida
NAIFID_DESDEMONA	710	Desdemona
NAIFID_JULIET	711	Juliet
NAIFID_PORTIA	712	Portia
NAIFID_ROSALIND	713	Rosalind
NAIFID_BELINDA	714	Belinda
NAIFID_PUCK	715	Puck
NAIFID_CALIBAN	716	Caliban
NAIFID_SYCORAX	717	Sycorax
NAIFID_PROSPERO	718	Prospero
NAIFID_SETEBOS	719	Setebos
NAIFID_STEPHANO	720	Stephano
NAIFID_TRINCULO	721	Trinculo
NAIFID_FRANCISCO	722	Francisco
NAIFID_MARGARET	723	Margaret
NAIFID_FERDINAND	724	Ferdinand
NAIFID_PERDITA	725	Perdita
NAIFID_MAB	726	Mab
NAIFID_CUPID	727	Cupid
NAIFID_NEPTUNE	899	Neptune
NAIFID_TRITON	801	Triton
NAIFID_NEREID	802	Nereid

continues on next page

Table 1 – continued from previous page

Predefined Macros	NAIF ID	Name
NAIFID_NAIAD	803	Naiad
NAIFID_THALASSA	804	Thalassa
NAIFID_DESPINA	805	Despina
NAIFID_GALATEA	806	Galatea
NAIFID_LARISSA	807	Larissa
NAIFID_PROTEUS	808	Proteus
NAIFID_HALIMEDE	809	Halimede
NAIFID_PSAMATHE	810	Psamathe
NAIFID_SAO	811	Sao
NAIFID_LAOMEDEIA	812	Laomedea
NAIFID_NESO	813	Neso
NAIFID_PLUTO	999	Pluto
NAIFID_CHARON	901	Charon
NAIFID_NIX	902	Nix
NAIFID_HYDRA	903	Hydra
NAIFID_KERBEROS	904	Kerberos
NAIFID_STYX	905	Styx

7.4 Comets

Predefined Macros	NAIF ID	Name
NAIFID_AREND	100001	Arend
NAIFID_AREND_RIGAUX	100002	Arend-Rigaux
NAIFID_ASHBROOK_JACKSON	100003	Ashbrook-Jackson
NAIFID_BOETHIN	100004	Boethin
NAIFID_BORRELLY	100005	Borrelly
NAIFID_BOWELL_SKIFF	100006	Bowell-Skiff
NAIFID_BRADFIELD	100007	Bradfield
NAIFID_BROOKS_2	100008	Brooks 2
NAIFID_BRORSEN_METCALF	100009	Brorsen-Metcalf
NAIFID_BUS	100010	Bus
NAIFID_CHERNYKH	100011	Chernykh
NAIFID_CHURYUMOV_GERASIMENKO	100012	Churyumov-Gerasimenko
NAIFID_CIFFREO	100013	Ciffreo
NAIFID_CLARK	100014	Clark
NAIFID_COMAS_SOLA	100015	Comas Sola
NAIFID_CROMMELIN	100016	Crommelin
NAIFID_D_ARREST	100017	D'Drrest
NAIFID_DANIEL	100018	Daniel
NAIFID_DE_VICO_SWIFT	100019	De Vico-Swift
NAIFID_DENNING_FUJIKAWA	100020	Denning-Fujikawa
NAIFID_DU_TOIT_1	100021	Du Toit 1
NAIFID_DU_TOIT_HARTLEY	100022	Du Toit-Hartley
NAIFID_DUTOIT_NEUJMIN_DELPORTE	100023	Dutoit-Neujmin-Delporte
NAIFID_DUBIAGO	100024	Dubiago
NAIFID_ENCKE	100025	Encke
NAIFID_FAYE	100026	Faye

continues on next page

Table 2 – continued from previous page

Predefined Macros	NAIF ID	Name
NAIFID_FINLAY	1000027	Finlay
NAIFID_FORBES	1000028	Forbes
NAIFID_GEHRELS_1	1000029	Gehrels 1
NAIFID_GEHRELS_2	1000030	Gehrels 2
NAIFID_GEHRELS_3	1000031	Gehrels 3
NAIFID_GIACOBINI_ZINNER	1000032	Giacobini-Zinner
NAIFID_GICLAS	1000033	Giclas
NAIFID_GRIGG_SKJELLERUP	1000034	Grigg-Skjellerup
NAIFID_GUNN	1000035	Gunn
NAIFID_HALLEY	1000036	Halley
NAIFID_HANEDA_CAMPOS	1000037	Haneda-Campos
NAIFID_HARRINGTON	1000038	Harrington
NAIFID_HARRINGTON_ABELL	1000039	Harrington-Abell
NAIFID_HARTLEY_1	1000040	Hartley 1
NAIFID_HARTLEY_2	1000041	Hartley 2
NAIFID_HARTLEY_IRAS	1000042	Hartley-Iras
NAIFID_HERSCHEL_RIGOLLET	1000043	Herschel-Rigollet
NAIFID_HOLMES	1000044	Holmes
NAIFID_HONDA_MRKOS_PAJDUSAKOVA	1000045	Honda-Mrkos-Pajdusakova
NAIFID_HOWELL	1000046	Howell
NAIFID_IRAS	1000047	Iras
NAIFID_JACKSON_NEUJMIN	1000048	Jackson-Neujmin
NAIFID_JOHNSON	1000049	Johnson
NAIFID_KEARNS_KWEE	1000050	Kearns-Kwee
NAIFID_KLEMOLA	1000051	Klemola
NAIFID_KOHOUTEK	1000052	Kohoutek
NAIFID_KOJIMA	1000053	Kojima
NAIFID_KOPFF	1000054	Kopff
NAIFID_KOWAL_1	1000055	Kowal 1
NAIFID_KOWAL_2	1000056	Kowal 2
NAIFID_KOWAL_MRKOS	1000057	Kowal-Mrkos
NAIFID_KOWAL_VAVROVA	1000058	Kowal-Vavrova
NAIFID_LONGMORE	1000059	Longmore
NAIFID_LOVAS_1	1000060	Lovas 1
NAIFID_MACHHOLZ	1000061	Machholz
NAIFID_MAURY	1000062	Maury
NAIFID_NEUJMIN_1	1000063	Neujmin 1
NAIFID_NEUJMIN_2	1000064	Neujmin 2
NAIFID_NEUJMIN_3	1000065	Neujmin 3
NAIFID_OLBERS	1000066	Olbers
NAIFID_PETERS_HARTLEY	1000067	Peters-Hartley
NAIFID_PONS_BROOKS	1000068	Pons-Brooks
NAIFID_PONS_WINNECKE	1000069	Pons-Winnecke
NAIFID_REINMUTH_1	1000070	Reinmuth 1
NAIFID_REINMUTH_2	1000071	Reinmuth 2
NAIFID_RUSSELL_1	1000072	Russell 1
NAIFID_RUSSELL_2	1000073	Russell 2
NAIFID_RUSSELL_3	1000074	Russell 3
NAIFID_RUSSELL_4	1000075	Russell 4
NAIFID_SANGUIN	1000076	Sanguin

continues on next page

Table 2 – continued from previous page

Predefined Macros	NAIF ID	Name
NAIFID_SCHAUMASSE	1000077	Schaumasse
NAIFID_SCHUSTER	1000078	Schuster
NAIFID_SCHWASSMANN_WACHMANN_1	1000079	Schwassmann-Wachmann 1
NAIFID_SCHWASSMANN_WACHMANN_2	1000080	Schwassmann-Wachmann 2
NAIFID_SCHWASSMANN_WACHMANN_3	1000081	Schwassmann-Wachmann 3
NAIFID_SHAJN_SCHALDACH	1000082	Shajn-Schaldach
NAIFID_SHOEMAKER_1	1000083	Shoemaker 1
NAIFID_SHOEMAKER_2	1000084	Shoemaker 2
NAIFID_SHOEMAKER_3	1000085	Shoemaker 3
NAIFID_SINGER_BREWSTER	1000086	Singer-Brewster
NAIFID_SLAUGHTER_BURNHAM	1000087	Slaughter-Burnham
NAIFID_SMIRNOVA_CHERNYKH	1000088	Smirnova-Chernykh
NAIFID_STEPHAN_OTERMA	1000089	Stephan-Oterma
NAIFID_SWIFT_GEHRELS	1000090	Swift-Gehrels
NAIFID_TAKAMIZAWA	1000091	Takamizawa
NAIFID_TAYLOR	1000092	Taylor
NAIFID_TEMPEL_1	1000093	Tempel 1
NAIFID_TEMPEL_2	1000094	Tempel 2
NAIFID_TEMPEL_TUTTLE	1000095	Tempel-Tuttle
NAIFID_TRITTON	1000096	Tritton
NAIFID_TSUCHINSHAN_1	1000097	Tsuchinshan 1
NAIFID_TSUCHINSHAN_2	1000098	Tsuchinshan 2
NAIFID_TUTTLE	1000099	Tuttle
NAIFID_TUTTLE_GIACOBINI_KRESAK	1000100	Tuttle-Giacobini-Kresak
NAIFID_VAISALA_1	1000101	Vaisala 1
NAIFID_VAN_BIESBROECK	1000102	Van Biesbroeck
NAIFID_VAN_HOUTEN	1000103	Van Houten
NAIFID_WEST_KOHOUTEK_IKEMURA	1000104	West-Kohoutek-Ikemura
NAIFID_WHIPPLE	1000105	Whipple
NAIFID_WILD_1	1000106	Wild 1
NAIFID_WILD_2	1000107	Wild 2
NAIFID_WILD_3	1000108	Wild 3
NAIFID_WIRTANEN	1000109	Wirtanen
NAIFID_WOLF	1000110	Wolf
NAIFID_WOLF_HARRINGTON	1000111	Wolf-Harrington
NAIFID_LOVAS_2	1000112	Lovas 2
NAIFID_URATA_NIJIMA	1000113	Urata-Nijima
NAIFID_WISEMAN_SKIFF	1000114	Wiseman-Skiff
NAIFID_HELIN	1000115	Helin
NAIFID_MUELLER	1000116	Mueller
NAIFID_SHOEMAKER_HOLT_1	1000117	Shoemaker-Holt 1
NAIFID_HELIN_ROMAN_CROCKETT	1000118	Helin-Roman-Crockett
NAIFID_HARTLEY_3	1000119	Hartley 3
NAIFID_PARKER_HARTLEY	1000120	Parker-Hartley
NAIFID_HELIN_ROMAN_ALU_1	1000121	Helin-Roman-Alu 1
NAIFID_WILD_4	1000122	Wild 4
NAIFID_MUELLER_2	1000123	Mueller 2
NAIFID_MUELLER_3	1000124	Mueller 3
NAIFID_SHOEMAKER_LEVY_1	1000125	Shoemaker-Levy 1
NAIFID_SHOEMAKER_LEVY_2	1000126	Shoemaker-Levy 2

continues on next page

Table 2 – continued from previous page

Predefined Macros	NAIF ID	Name
NAIFID_HOLT_OLMSTEAD	1000127	Holt-Olmstead
NAIFID_METCALF_BREWINGTON	1000128	Metcalf-Brewington
NAIFID_LEVY	1000129	Levy
NAIFID_SHOEMAKER_LEVY_9	1000130	Shoemaker-Levy 9
NAIFID_HYAKUTAKE	1000131	Hyakutake
NAIFID_HALE_BOPP	1000132	Hale-Bopp
NAIFID_SIDING_SPRING	1003228	Siding Spring

RELEASE NOTES

- **Version 4.0.4**

Fix the `calceph_gettimespan` function result with non-integer time bounds in SPICE kernel files.
Support for parallel execution of the python and octave tests.

- **Version 4.0.3**

Fix a crash of the function `calceph_open` and `calceph_open_array` with some invalid SPICE kernel files (files `.tpc` and `.tf`) on arm32v6 processors.
Add the man pages for the tools.
Replace the calls to `sprintf` by the calls to the fortified function `snprintf`.
Version 4.0.2 skipped due to an archive problem.

- **Version 4.0.1**

Fix the function `calceph_open` and `calceph_open_array` with some SPICE kernel files (files `.bsp` and `.spk`) if the segment descriptor does not contain any segments.

- **Version 4.0.0**

Use `cmake` to compile the library. Binary ABI may be broken by this major change in the compilation process. The library remains compatible at the source level: the existing application therefore only needs a recompilation.
Add the function `calceph_getidbyname` and `calceph_getnamebyidss`.
Fix potential crash of `fortran-90` interface only, on 32-bit OS, if `ephemeris` file does not exist.
Support frame name with any character except tab, space, comma, parentheses, equal, in the frame SPICE kernel file (files `.tf`).
Fix system error messages to be thread-safe (remove `strerror`).
Fix memory buffer overflow if the number of constants is greater than 400 in the original JPL files.

- **Version 3.5.5**

Fix memory leaks when files are closed.
Fix heap buffer overflow (read only operation) with text SPICE kernel files.
Fix memory crash if the SPICE kernel files contain segments with a size of the directory greater than 100.

- **Version 3.5.4**

Fix the documentation about the unsupported segment 19.
Fix the window size if requested time is near a boundary for SPICE kernel files containing segments of type 18, compliant with the SPICE specifications.
Fix incorrect results for SPICE kernel files containing segments of type 20.
Support the segment 14 in the SPICE kernel file.

- **Version 3.5.3**

Fix compilation error with Cython 3.0 or later.
Fix compilation error with Python 3.10 or later on some linux distributions.
Fix the tests suite with octave, due to a change of the syntax parsing by octave.

- **Version 3.5.2**

Fix a possible buffer overflow in the python interface of getfileversion.
Fix the undefined external symbol rint with visual C compiler 10.0.
Fix the redefinition of vasprintf with the environment MinGW.

- **Version 3.5.1**

Support the incremental assignment in the text SPICE kernel file (files .tpc).
Support the relative frames in the frame SPICE kernel file (files .tf).
Fix the returned values of calceph_getconstantvs with large SPICE kernels.
Fix random crash or double-free error when meta-kernel SPICE kernel files are closed (files .mk).
Raise an error inside the function calceph_compute if center != 0 for the target (14,15,16,17), to conform to the documentation.
Fix the object name Megaclite (519) from NAIFID_MAGACLITE to NAIFID_MEGACLITE.

- **Version 3.5.0**

Add the function calceph_getmaxsupportedorder, calceph_getpositionrecordindex2 and calceph_getorientrecordindex2.
Update config.sub and config.guess to support new processors.
Fix an incorrect result of calceph_(s)getconstant and calceph_getconstantvd with SPICE text kernel if the current locale has a decimal separator different than the decimal point (e.g. comma).
Fix compilation warnings with gcc 11 about pointers and arrays.
Fix the installation with python 3.10 or later (PEP 632).
Fix compilation errors with the android SDK API level < 24.
Reduce the stack size of the arrays for the evaluation with C99 compilers.
Change the array size of the function calceph_getfileversion from the value CALCEPH_MAX_CONSTANTNAME to CALCEPH_MAX_CONSTANTVALUE, to conform to the documentation and examples.
Only C and Fortran 2003 are affected by this change : previous header file contains an invalid declaration of the function.
Few programs may be affected by this change, as the required array has a smaller size : No buffer overflow may appear.

- **Version 3.4.7**

Fix a decode error of the little-endian SPICE kernel files on the big-endian architectures (e.g. processor s390x).
Fix the transmission of the flags FCFLAGS to the fortran compilers.

- **Version 3.4.6**

Fix a wrong error message about unsupported order for the segment 21.
Fix incorrect results for SPICE kernel files containing segments of type 21 with many records (>=100) and improved the accuracy if segments of type 21 contain few records (<100).

- **Version 3.4.5**

Fix a random crash of calceph_open_array if one of the file is invalid.
f90calceph_seterrorhandler now ignores the parameter userfunc, instead of the requirement to set to 0, if the parameter type is 1 or 2. userfunc can be an empty function. It fixes compilation errors with gcc 10.1.

- **Version 3.4.4**

- Fix a regression introduced in 3.4.3 (remove a recursion with SPICE kernel files).

- **Version 3.4.3**

- Remove a recursion to read the segments of the SPICE kernel files. It reduces the usage of the stack.
 - Fix the installation of python package under Anaconda.

- **Version 3.4.2**

- Add a missing makefile for windows system using the Visual C++ compiler.
 - Support SPICE kernels larger than 4GBytes.

- **Version 3.4.1**

- Improve the execution time of calceph_open and calceph_open_array if the spice kernels contains a large number of bodies.
 - Update config.sub and config.guess to support arm processors.

- **Version 3.4.0**

- Add the function calceph_isthreadsafe.
 - Multiple threads can now access the same ephemeris descriptor if the function calceph_isthreadsafe returns 1.
 - Fortran and C examples (f2003parallel.f, cparallel.c), written using OpenMP, are available in the folder examples.
 - Fix an error if multiple SPICE kernels are loaded for the same objects over different time-span.
 - Fix the MinGW Makefiles if the variable MAKE contains spaces.
 - Support the segment 5 and 18 in the SPICE kernel file.
 - Support the euler angles for the orientation stored in a text PCK files (BODY..._POLE_RA, BODY..._POLE_DE, BODY..._POLE_PM, BODY..._NUT_PREC_...).
 - Support the frame 17 (ECLIPJ2000) in the SPICE kernel file.
 - Add the utilities calceph_queryposition and calceph_queryorientation.

- **Version 3.3.1**

- Fix the installation with python 3.7.0 or later.
 - Fix the installation with python and pip on Windows operating system.
 - Add the missing file pythonapi/src/Makefile.mingw for the environment MinGW.

- **Version 3.3.0**

- Add the functions calceph_getfileversion.
 - Fix a regression to open some old JPL DE format files.
 - Fix a compiler warning in the file util.c.
 - Support the segments 8, 9, 17 and 21 in the SPICE kernel file.
 - Check the validity of the number of constants in the original INPOP/DE files.
 - For the Python interface, the functions compute??? and orient??? supports now a list or numpy's array for the time parameters.

- **Version 3.2.0**

- Fix the creation of the dynamic library with msys/mingw on Windows.
 - Fix the returned value of the functions f90calceph_getconstantvd and f90calceph_getconstantvs.
 - Fix a compilation warning with the GNU C compilers 8.0 or later.
 - Support the original JPL files with TT-TDB or with a large number of constants.
 - Support the IAU 1980 Nutation Angles of the JPL files.

Add the NAIF identification numbers for DIA, KERBEROS, STYX and SIDING SPRING.

Add the option `installnodoc` to the make command.

- **Version 3.1.0**

Add the Mex interface compliant with Octave 4.0+ and Matlab 2017+.

Add the functions `calceph_getconstantsd`, `calceph_getconstantvd` and `calceph_getconstantss` and `calceph_getconstantvs`.

Fix a compilation problem with MinGW if the terminal `cmd.exe` is used.

Fix a wrong function name `open_array` instead of `open` in the documentation of the Python interface.

Fix the return value of the functions `calceph_orient_xxx` when the unit `CALCEPH_UNIT_RAD` is not provided.

The return value of the function `calceph_(s)getconstant(index)` is the number of values associated to the constant.

Display a better message for the unsupported old spice kernel (NAIF/DAF)

- **Version 3.0.0**

Update the license CeCILL v2.0 to CeCILL v2.1.

Fix a decode error for SPICE kernels with a big-endian format.

Add the function `calceph_gettimescale` and `calceph_gettimespan`.

Add the function `calceph_getpositionrecordcount` and `calceph_getpositionrecordindex`.

Add the function `calceph_getorientrecordcount` and `calceph_getorientrecordindex`.

Add the function `calceph_sgettimescale` and `calceph_sgettimespan`.

Support INPOP file format 3.0 (add angular momentum due to the rotation in the binary file).

Use `sphinx-doc` to produce the documentation.

- **Version 2.3.2**

Fix the return value of the function `calceph_getconstant` if the constant name "AU" or "EMRAT" is not available.

Fix the documentation for the fortran interface of the function `calceph_prefetch`.

Fix the return value of the function `calceph_orient_unit` if the frame SPICE kernel file is missing.

- **Version 2.3.1**

Fix the compilation warnings with the Pelles compiler.

Fix the compilation warnings with the C89 standard.

Fix the compilation warnings with the GNU C compilers.

Fix the documentation for the constant `CALCEPH_VERSION_STRING`.

- **Version 2.3.0**

Add the python interface compliant with python 2.6+ and python 3.

Add the preprocessor macro `CALCEPH_VERSION_STRING`.

Add the function `calceph_getversion_str`.

Add the function `calceph_compute_order` and `calceph_orient_order`.

Fix the return value of the functions `calceph_compute_xxx` when the reference frame is not available in the spice kernel files.

The function should produce an error and return 0 (before the function performed no computation but it returned 1).

- **Version 2.2.5**

Fix an incorrect result if `CALCEPH_UNIT_DAY` is provided to `calceph_compute_unit` and the target is TCG-TCB or TT-TDB.

Support the numerical constants declared without parenthesis in the text kernel files (.tpc).
Support the segment 1, 12 and 13 in the SPICE kernel file.

- **Version 2.2.4**

Update the version number of the dynamic library.

- **Version 2.2.3**

Add the predefined constants for calceph version in the fortran interface.
Fix the build chain if calceph is compiled from another folder.

- **Version 2.2.2**

Support the compilation in the standard C89.

- **Version 2.2.1**

Remove debug informations that are printed when errors occur in calceph_?compute_???.
Support the Portland compilers.
Fix the info documentation.
Report an error if no asteroid is available in an ephemeris file with the INPOP file format (instead of a crash).

- **Version 2.2.0**

Support the new segments 20, 102, 103 and 120 in the SPICE kernel file.
Support the NAIF identification numbers.
Add the functions calceph_orient_unit and calceph_prefetch.

- **Version 2.1.0**

Fix a bug in calceph_getconstant and calceph_sgetconstant with an invalid name
Remove the null character in the name of the constant returned by the function (f90)calceph_(s)getconstantindex when the Fortran interface is used.

- **Version 2.0.0**

Fix memory leaks in calceph_open when errors occur.
Support INPOP file format 2.0 (supports TCB ephemeris file and add asteroids in the binary file).
Add the function calceph_open_array and calceph_compute_unit.
Add the tools calceph_inspector to show details about ephemeris file.
Support SPICE kernel file (SPK with segment 2 or 3, text and binary PCK, meta kernel, basic frame kernel).
Improve the performances.
Correct the Fortran 2003 interface for calceph_sgetconstantindex.
Add the constant 17 to get TCG-TCB from TCB ephemeris file.

- **Version 1.2.0**

Change the licensing : triple licenses to support integration in BSD software.
Remove explicit dependencies on the record size for DExxx.

- **Version 1.1.2**

Fix a compilation warning with oracle studio compiler 12.
Fix a bug with gcc on solaris in 64 bit mode.
Fix the copyright statements.

- **Version 1.1.1**

Fix a compilation error in util.h and a warning with the sun studio compilers.

- **Version 1.1.0**

Add the function calceph_seterrorhandler for the custom error handlers.

- **Version 1.0.3**

Support the JPL ephemeris file DE423.

- **Version 1.0.2**

Fix memory leaks in the fortran-90 interface.

- **Version 1.0.1**

Support the large ephemeris files (>2GB) on 32-bit operating systems.

Fix the documentation of the function f90calceph_sopen.

Fix an invalid open mode on Windows operating systems.

Report accurately the I/O errors.

- **Version 1.0.0**

Initial release.

REPORTING BUGS

If you think you have found a bug in the CALCEPH Library, first have a look on the CALCEPH Library web page <https://www.imcce.fr/inpop>, in which case you may find there a workaround for it. Otherwise, please investigate and report it. We have made this library available to you, and it seems very important for us, to ask you to report the bugs that you find.

There are a few things you should think about when you put your bug report together. You have to send us a test case that makes it possible for us to reproduce the bug. Include instructions on the way to run the test case.

You also have to explain what is wrong; if you get a crash, or if the results printed are incorrect and in that case, in what way.

Please include compiler version information in your bug report. This can be extracted using `cc -V` on some machines, or, if you're using `gcc`, `gcc -v`. Also, include the output from `uname -a` and the CALCEPH version.

Send your bug report to: inpop.imcce@obspm.fr. If you think something in this manual is unclear, or downright incorrect, or if the language needs to be improved, please send a note to the same address.

CALCEPH LIBRARY COPYING CONDITIONS

Copyright 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 2023, 2024

CNRS, Observatoire de Paris, Observatoire de la Côte d'Azur

Contributed by

Gastineau M. , Laskar J., Manche H., Astronomie et Systèmes Dynamiques, IMCCE, CNRS, Observatoire de Paris, UPMC

Fienga A. , Observatoire de la Côte d'Azur

inpop.imcce@obspm.fr

This library is governed by the CeCILL-C, CeCILL-B or CeCILL version 2 license under French law and abiding by the rules of distribution of free software. You can use, modify and/ or redistribute the software under the terms of the CeCILL-C, CeCILL-B or CeCILL version 2 license as circulated by CEA, CNRS and INRIA at the following URL "<http://www.cecill.info>".

As a counterpart to the access to the source code and rights to copy, modify and redistribute granted by the license, users are provided only with a limited warranty and the software's author, the holder of the economic rights, and the successive licensors have only limited liability.

In this respect, the user's attention is drawn to the risks associated with loading, using, modifying and/or developing or reproducing the software by the user in light of its specific status of free software, that may mean that it is complicated to manipulate, and that also therefore means that it is reserved for developers and experienced professionals having in-depth computer knowledge. Users are therefore encouraged to load and test the software's suitability as regards their requirements in conditions enabling the security of their systems and/or data to be ensured and, more generally, to use and operate it in the same conditions as regards security.

The fact that you are presently reading this means that you have had knowledge of the CeCILL-C, CeCILL-B or CeCILL version 2.1 license and that you accept its terms.